

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

+ 215
dp

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DEC 24 1992

WELL API NO. 30-005-62934
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LG-4334
7. Lease Name or Unit Agreement Name Sparrow SP State
8. Well No. 4
9. Pool name or Wildcat Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION	3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter <u>E</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>West</u> Line Section <u>5</u> Township <u>7S</u> Range <u>25E</u> NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3985' GR			

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Perforate, Treat <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4250'. Reached TD 12-12-92. Ran 95 joints 4-1/2" 10.5# J-55 ST&C casing set 4250'. Float shoe set 4250', float collar set 4205'. Cemented w/425' sx Super "C" w/5% Salt, .35% CF-2, 83/sx Hiseal, PD 9:30 PM 12-13-92. Bumped plug to 1100 psi for 30 minutes, float and casing held OK. Ran 1600' of 1", cemented w/300 sx 65/35/6. Perforated 3694-3843' w/20 .42" holes as follows: 3694, 95, 3703, 04, 05, 06, 07, 08, 09, 23, 24, 25, 37, 3801, 02, 29, 30, 31, 42 and 3843'. Acidized perfs 3801-43' w/1500g. 7 1/2% NEFE. Acidized perfs 3694-3737' w/1500g. 7 1/2% NEFE. Frac'd perfs 3694-3843' w/60000g. linear gel and 120000# 20/40 brady sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 12-21-92
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use) ORIGINAL SIGNED BY

WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE _____ DATE DEC 30 1992

CONDITIONS OF APPROVAL, IF ANY: