WW 011 Cons. Commis. M

Diamer III

Form 3160-5 (June 1990)

**UNITED STATES** DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135 artesia. m

DIDEALLOELA	AND MANAGEMENT	f. T D
BUREAU OF LA	AND MANAGEMENT	5. Lease Designation and Serial No.
SUNDRY NOTICES A	ND REPORTS ON WELLS	NM-36715
	or to deepen or reentry to a different rese	6. If Indian, Allottee or Tribe Name
	PERMIT—" for such proposals	
	N TRIPLICATE	7. If Unit or CA, Agreement Designation
SUBMIT I	N TRIPLICATE	To the or or, regression benefit and
Type of Well	1 1 1933	<del></del>
Oil Gas C	MARICO	8. Well Name and No.
Name of Operator	O. C. William	Blackwater Unit #3
YATES PETROLEUM CORPORATION	(505) 743-1471)	9. API Well No.
Address and Telephone No.		30-005-62946
105 South 4th St., Artesia, NM	1 88210	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey Desc		Wildcat Abo
Unit I, 1980' FSL & 660' FEL o	of Section 7-T9S-R22E	11. County or Parish, State
		Chaves Co., NM
CHECK ADDRODRIATE BOY(e)	TO INDICATE NATURE OF NOTICE, F	
CHECK APPROPRIATE BOX(S)	TO INDICATE NATURE OF NOTICE, I	TEL OIT, OIT OTHER DATA
TYPE OF SUBMISSION	TYPE OF A	CTION
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
XX Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	VVa. Coud & Cumface C	asing Dispose Water
	XX Other Spud & Surface Co	
give subsurface locations and measured and true vertical	pertinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40 of 20 conductions	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled,
Spudded a 26" hole at 3:15 PM surface. Resumed drilling 12 Ran 24 joints of 8-5/8" 24# J-Pattern notched guide shoe set 200 sacks "H", 12% Thixadd, 10 250 sacks Pacesetter Lite "C", 12.7). Tailed in with 200 sack AM 2-21-93. Bumped plug to 40 Ran Temperature Survey and fou sacks "C" and 3% CaCl2. PD 12	pertinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40 of 20 conductions	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled, tor pipe. Ready-Mix to  t at 992'. 1-Texas 950'. Cemented with yield 1.55, weight 14.6), 12 (yield 1.8, weight , weight 14.8). PD 5:15 ulate. WOC 6 hours. 1". Cemented with 140 Drilled out at 7:15 PM
Spudded a 26" hole at 3:15 PM surface. Resumed drilling 12 Ran 24 joints of 8-5/8" 24# J-Pattern notched guide shoe set 200 sacks "H", 12% Thixadd, 10 250 sacks Pacesetter Lite "C", 12.7). Tailed in with 200 sack AM 2-21-93. Bumped plug to 40 Ran Temperature Survey and fou sacks "C" and 3% CaCl2. PD 12	retinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40' of 20" conduction of 20" casing set at 992'. Insert float set at 10"/sack gilsonite and 2% CaCl2 (1/4"/sack celloseal and 2% CaCl2 (2.1/4"/sack celloseal and 2% CaCl2 (2.1/	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled, tor pipe. Ready-Mix to  t at 992'. 1-Texas 950'. Cemented with yield 1.55, weight 14.6), 12 (yield 1.8, weight , weight 14.8). PD 5:15 ulate. WOC 6 hours. 1". Cemented with 140 Drilled out at 7:15 PM
Spudded a 26" hole at 3:15 PM surface. Resumed drilling 12 Ran 24 joints of 8-5/8" 24# J-Pattern notched guide shoe set 200 sacks "H", 12% Thixadd, 10 250 sacks Pacesetter Lite "C", 12.7). Tailed in with 200 sack AM 2-21-93. Bumped plug to 40 Ran Temperature Survey and fou sacks "C" and 3% CaCl2. PD 12	retinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40' of 20" conduction of 20" casing set at 992'. Insert float set at 10"/sack gilsonite and 2% CaCl2 (1/4"/sack celloseal and 2% CaCl2 (2.1/4"/sack celloseal and 2% CaCl2 (2.1/	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled, tor pipe. Ready-Mix to  t at 992'. 1-Texas 950'. Cemented with yield 1.55, weight 14.6), 12 (yield 1.8, weight , weight 14.8). PD 5:15 ulate. WOC 6 hours. 1". Cemented with 140 Drilled out at 7:15 PM
Spudded a 26" hole at 3:15 PM surface. Resumed drilling 12.  Ran 24 joints of 8-5/8" 24# J-Pattern notched guide shoe set 200 sacks "H", 12% Thixadd, 10 250 sacks Pacesetter Lite "C", 12.7). Tailed in with 200 sac AM 2-21-93. Bumped plug to 40 Ran Temperature Survey and fou sacks "C" and 3% CaCl2. PD 12 2-21-93. Nippled up and teste	retinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40' of 20" conduction of 20" casing set at 992'. Insert float set at 10"/sack gilsonite and 2% CaCl2 (1/4"/sack celloseal and 2% CaCl2 (2.1/4"/sack celloseal and 2% CaCl2 (2.1/	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled, tor pipe. Ready-Mix to  t at 992'. 1-Texas 950'. Cemented with yield 1.55, weight 14.6), 12 (yield 1.8, weight , weight 14.8). PD 5:15 ulate. WOC 6 hours. 1". Cemented with 140 Drilled out at 7:15 PM
Spudded a 26" hole at 3:15 PM surface. Resumed drilling 12.  Ran 24 joints of 8-5/8" 24# J-Pattern notched guide shoe set 200 sacks "H", 12% Thixadd, 10 250 sacks Pacesetter Lite "C", 12.7). Tailed in with 200 sac AM 2-21-93. Bumped plug to 40 Ran Temperature Survey and four sacks "C" and 3% CaCl2. PD 12 2-21-93. Nippled up and teste	retinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40' of 20" conduction of 20" casing set at 992'. Insert float set at 20"/sack gilsonite and 2% CaCl2 (2.1/4*/sack celloseal and 2% CaCl2 (2.2 cks "C" and 2% CaCl2 (yield 1.32 of 20 psi, OK. Cement did not circulated top of cement at 150'. Rand 2:15 PM 2-21-93. WOC 14 hours. Red to 1000*/s, OK. Reduced hole to 20.1 cks "C" and 20.2 cks "C" and 20.3 cks "C" and 20.3 cks "C" and 20 psi, OK. Reduced hole to 20.3 cks "C" and 20.3 cks "C" and 20.3 cks "C" and 20 psi, OK. Reduced hole to 20.3 cks "C" and 20.3 cks "C" and 20.3 cks "C" and 20 psi, OK. Reduced hole to 20.3 cks "C" and 20.3 cks "C" and 20.3 cks "C" and 20 psi, OK. Reduced hole to 20.3 cks "C" and 20.3 cks "C" an	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled, tor pipe. Ready-Mix to  t at 992'. 1-Texas 950'. Cemented with yield 1.55, weight 14.6), 12 (yield 1.8, weight , weight 14.8). PD 5:15 ulate. WOC 6 hours. 1". Cemented with 140 Drilled out at 7:15 PM o 7-7/8". Resumed drilling.
Spudded a 26" hole at 3:15 PM surface. Resumed drilling 12.  Ran 24 joints of 8-5/8" 24# J-Pattern notched guide shoe set 200 sacks "H", 12% Thixadd, 10 250 sacks Pacesetter Lite "C", 12.7). Tailed in with 200 sac AM 2-21-93. Bumped plug to 40 Ran Temperature Survey and four sacks "C" and 3% CaCl2. PD 12 2-21-93. Nippled up and tested of the sacks "C" and 3% CaCl2. Signed Thereby certify that the foregoing is true-and correct Signed Thereby certify the signed Thereby certify the signed Thereby certify the signed Thereby certification the signed Thereby	ertinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40' of 20" conduction-1/4" hole 8:00 PM 2-19-93.  55 8rd ST&C (997') of casing set at 992'. Insert float set at 10#/sack gilsonite and 2% CaCl2 (1/4#/sack celloseal and 2% CaCl2 (2/1/4#/sack celloseal and 2% CaCl	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled, tor pipe. Ready-Mix to  t at 992'. 1-Texas 950'. Cemented with yield 1.55, weight 14.6), 12 (yield 1.8, weight , weight 14.8). PD 5:15 ulate. WOC 6 hours. 1". Cemented with 140 Drilled out at 7:15 PM o 7-7/8". Resumed drilling.
Spudded a 26" hole at 3:15 PM surface. Resumed drilling 12.  Ran 24 joints of 8-5/8" 24# J-Pattern notched guide shoe set 200 sacks "H", 12% Thixadd, 10 250 sacks Pacesetter Lite "C", 12.7). Tailed in with 200 sack AM 2-21-93. Bumped plug to 40 Ran Temperature Survey and fou sacks "C" and 3% CaCl2. PD 12 2-21-93. Nippled up and teste	ertinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40' of 20" conduction-1/4" hole 8:00 PM 2-19-93.  55 8rd ST&C (997') of casing set at 992'. Insert float set at 10#/sack gilsonite and 2% CaCl2 (1/4#/sack celloseal and 2% CaCl2 (2/1/4#/sack celloseal and 2% CaCl	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled, tor pipe. Ready-Mix to  t at 992'. 1-Texas 950'. Cemented with yield 1.55, weight 14.6), 12 (yield 1.8, weight , weight 14.8). PD 5:15 ulate. WOC 6 hours. 1". Cemented with 140 Drilled out at 7:15 PM o 7-7/8". Resumed drilling.
Spudded a 26" hole at 3:15 PM surface. Resumed drilling 12.  Ran 24 joints of 8-5/8" 24# J-Pattern notched guide shoe set 200 sacks "H", 12% Thixadd, 10 250 sacks Pacesetter Lite "C", 12.7). Tailed in with 200 sack AM 2-21-93. Bumped plug to 40 Ran Temperature Survey and four sacks "C" and 3% CaCl2. PD 12 2-21-93. Nippled up and tested the sacks "C" and 3% CaCl2 and tested the sacks "C" and the sacks "C" and the sacks "C" and 3% CaCl2. PD 12 2-21-93. Nippled up and tested the sacks "C" and sacks "C" a	ertinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40' of 20" conduction-1/4" hole 8:00 PM 2-19-93.  55 8rd ST&C (997') of casing set at 992'. Insert float set at 10#/sack gilsonite and 2% CaCl2 (1/4#/sack celloseal and 2% CaCl2 (2/1/4#/sack celloseal and 2% CaCl	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled, tor pipe. Ready-Mix to  t at 992'. 1-Texas 950'. Cemented with yield 1.55, weight 14.6), 12 (yield 1.8, weight , weight 14.8). PD 5:15 ulate. WOC 6 hours. 1". Cemented with 140 Drilled out at 7:15 PM o 7-7/8". Resumed drilling.
Spudded a 26" hole at 3:15 PM surface. Resumed drilling 12.  Ran 24 joints of 8-5/8" 24# J-Pattern notched guide shoe set 200 sacks "H", 12% Thixadd, 10 250 sacks Pacesetter Lite "C", 12.7). Tailed in with 200 sac AM 2-21-93. Bumped plug to 40 Ran Temperature Survey and four sacks "C" and 3% CaCl2. PD 12 2-21-93. Nippled up and tested the space of Federal or State office use)	retinent details, and give pertinent dates, including estimated date depths for all markers and zones pertinent to this work.)*  2-18-93. Set 40' of 20" conduction conduction of 20	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) of starting any proposed work. If well is directionally drilled, tor pipe. Ready-Mix to  t at 992'. 1-Texas 950'. Cemented with yield 1.55, weight 14.6), 12 (yield 1.8, weight , weight 14.8). PD 5:15 ulate. WOC 6 hours. 1". Cemented with 140 Drilled out at 7:15 PM o 7-7/8". Resumed drilling.