

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., of Survey Description)

660' FSL & 990' FEL of Section 17-T8S-R22E (Unit P, SESE)

5. Lease Designation and Serial No.

NM-36724

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Salt Creek Unit #9

9. API Well No.

30-005-62953

10. Field and Pool, or Exploratory Area

West Pecos Slope Abo

11. County or Parish, State

Chaves Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Surface casing & cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Resumed drilling a 12-1/4" hole with rotary tools at 9:00 PM 12-21-94. Reached TD of 12-1/4" hole at 6:15 PM 12-23-94. Ran 21 joints of 8-5/8" 24# 8rd J-55 ST&C (929.18') of casing set at 927'. 1-Texas Pattern notched guide shoe set at 927'. Insert float set at 883.70'. Cemented with 150 sacks "H", 12% thixad, 1/4#/sack celloseal, 10#/sack gilsonite and 2% CaCl2 (yield 1.52, weight 14.6) and 350 sacks Pacesetter Lite C, 1/4#/sack celloseal, 10#/sack gilsonite and 3% CaCl2 (yield 1.99, weight 12.5). Tailed in with 250 sacks Class C 2% CaCl2 (yield 1.34, weight 14.8). PD 12:45 AM 12-24-94. Bumped plug to 800 psi, OK. Cement did not circulate. WOC 5 hours. Ran Temperature Survey and found top of cement at 180'. Ran 1". Tagged cement at 110'. Spotted 50 sacks "H", 12% thixad, 1/4#/sack celloseal, 10#/sack gilsonite and 2% CaCl2. PD 8:30 AM 12-26-94. WOC 1 hour. Ran 1". Tagged cement at 110'. Spotted 50 sacks "H", 12% thixad, 1/4#/sack celloseal, 10#/sack gilsonite and 2% CaCl2. PD 10:30 AM 12-26-94. WOC 3-1/2 hours. Ran 1". Tagged cement at 110'. Filled hole with 2 yards of Ready-Mix. NOTE: Received permission from J.R. Hogwood with BLM in Roswell to ready mix to surface. PD 2:30 PM 12-26-94. WOC. Drilled out at 9:00 PM 12-26-94. WOC 68 hours and 15 minutes. Nipped up and tested to 1000# for 30 minutes. Reduced hole to 7-7/8". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed

*Kurtis Kleen*

Title Production Clerk

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date January 4, 1995

Date

JAN 10 1995

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side