

NM Oil Cons. Commission  
Drawer DD  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
Artesia, NM 88210

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-18484

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Unruh AFF Federal #1

9. API Well No.

30-005-62957

10. Field and Pool, or Exploratory Area

Pecos Slope Abo

11. County or Parish, State

Chaves Co., NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471 P. C. D.

ARTESIA, OFFICE

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL & 1530' FEL of Section 20-T10S-R25E (Unit B, NWNE)

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Production Casing & cement

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 4400'. Reached TD at 1:30 AM 6-3-94. Ran 105 joints of 4-1/2" casing as follows: 16 joints of 4-1/2" 10.5# J-55 sandblasted (655.18') and 89 joints of 4-1/2" 10.5# J-55 mill varnish (3758.34') (Total 4413.52') of casing set at 4400'. Davis Lynch regular guide shoe set at 4400'. Davis Lynch float collar set at 4358'. Cemented as follows: 20 bbls H2O, 20% J-4, 2 gallons LT-32, 50# Adomite Aqua, 350 sacks Super "C" 61-15-11, 5#/sack salt, .35% CF-2 and 8#/sack Hiseal (yield 1.76, weight 13.0). PD 8:05 AM 6-4-94. Bumped plug to 1500 psi for 2 minutes. WOC. Released rig at 10:00 AM 6-4-94. NOTE: Marker joint set at 3744-3763'. Centralizers set at 4315', 4187, 4060, 3983, 3806 & 3660'.

Waiting on completion unit.

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Clerk

Date June 7, 1994

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

JUN 9 1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side