

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-62960
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Presler Lake
8. Well No. #4
9. Pool name or Wildcat Many Gates-San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4004' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Hanson Operating Company, Inc. ✓
3. Address of Operator P.O. Box 1515, Roswell, New Mexico 88202-1515
4. Well Location Unit Letter B : 1650 Feet From The East Line and 330 Feet From The North Line Section 12 Township 9S Range 29E NMPM Chaves County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran and cemented 7" 23# ST&C J-55 casing as follows:

Guide shoe, 1jt 7" casing, Float Shoe, 96 jt 7" casing. Set at 3120'.  
Cement with 500sx Premium Plus "C" w/2% Cacl. Plug down at 9:40P 5/26/93.  
Test to 950#. Held OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Patricia A. McGraw TITLE Production Analyst DATE 6/18/93

TYPE OR PRINT NAME Patricia A. McGraw TELEPHONE NO. 505/622-7331

(This space for State Use) ORIGINAL SIGNED BY

APPROVED BY MIKE WILLIAMS TITLE DIRECTOR DATE JUN 24 1993

CONDITIONS OF APPROVAL, IF ANY: