

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-62967
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2925
7. Lease Name or Unit Agreement Name Trailblazer ANL State
8. Well No. 1
9. Pool name or Wildcat Southeast Acme San Andres

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	RECEIVED OCT 18 1993
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South Fourth Street - Artesia, NM 88210	
4. Well Location Unit Letter <u>0</u> : <u>330</u> Feet From The <u>South</u> Line and <u>1650</u> Feet From The <u>East</u> Line Section <u>11</u> Township <u>8S</u> Range <u>27E</u> NMPM Chaves County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3929' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole at 7:30 AM 7-5-93.

TD 458'. Ran 10 joints of 8-5/8" 24# J-55 (458') of casing set at 458'. 1-Texas Pattern notched guide shoe set at 458'. Insert float set at 415'. Cemented with 200 sacks Class "C", 1/4# celloseal and 2% CaCl₂ (yield 1.33, weight 14.8). Tailed in with 100 sacks Class "C" 2% CaCl₂ (yield 1.32, weight 14.8). PD 6:40 PM 7-5-93. Bumped plug to 600 psi, OK. Circulated 75 sacks. WOC. Drilled out at 12:00 Noon 7-6-93. WOC 17 hours and 20 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE Oct. 12, 1993
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505-748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE OCT 29 1993

CONDITIONS OF APPROVAL, IF ANY: