

c15r  
DPDISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

AUG 11 1993

|   |
|---|
| WELL API NO.<br>30-005-62968  |
| 5. Indicate Type of Lease<br>STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No.<br>VB-233  |
| 7. Lease Name or Unit Agreement Name<br>Carl ANO State  |
| 8. Well No.<br>1  |
| 9. Pool name or Wildcat<br>South East Acme San Andres   |

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

|  |   |
|--|---|
| 1. Type of Well:<br>OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER | 2. Name of Operator<br>YATES PETROLEUM CORPORATION  |
| 3. Address of Operator<br>105 South 4th St., Artesia, NM 88210   | 4. Well Location<br>Unit Letter 0 : 330 Feet From The South Line and 2310 Feet From The East Line<br>Section 1 Township 8S Range 27E NMPM Chaves County |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.)<br>3967' GR   |   |

|   |  |
|---|--|
| 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data |  |
| NOTICE OF INTENTION TO:   | SUBSEQUENT REPORT OF:                                      |
| PERFORM REMEDIAL WORK <input type="checkbox"/>                                | PLUG AND ABANDON <input type="checkbox"/>                  |
| TEMPORARILY ABANDON <input type="checkbox"/>                                  | CHANGE PLANS <input type="checkbox"/>                      |
| PULL OR ALTER CASING <input type="checkbox"/>                                 | OTHER: <input type="checkbox"/>                            |
| OTHER: <input type="checkbox"/>   | OTHER: Casing & cement <input checked="" type="checkbox"/> |

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 455'. Ran 10 joints of 8-5/8" 24# J-55 (455') of casing set at 455'. 1-Texas Pattern notched guide shoe set at 455'. Insert float set at 408'. Cemented with 200 sacks Class "C", 1/4#/sack celloseal and 2% CaCl<sub>2</sub> (yield 1.32, weight 14.8). Tailed in with 100 sacks Class "C" 2% CaCl<sub>2</sub> (yield 1.32, weight 14.8). PD 11:45 AM 7-16-93. Bumped plug to 700 psi, OK. Circulated 90 sacks. WOC. Drilled out at 11:30 AM 7-17-93. WOC 23 hours and 45 minutes. Nippled up and tested to 750# for 30 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE August 7, 1993TYPE OR PRINT NAME Rusty KleinTELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE AUG 6 1993

CONDITIONS OF APPROVAL, IF ANY: