

clst
dp

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-62976
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-233
7. Lease Name or Unit Agreement Name Carl ANO State
8. Well No. 4
9. Pool name or Wildcat South East Acme San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter M : 330 Feet From The South Line and 990 Feet From The West Line Section 1 Township 8S Range 27E NMMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3967' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: Spud & surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded an 8" hole at 3:00 PM 7-31-93. Drilled 10'. NOTE: Notified Gary Williams with NMOCD - Artesia of spud.

8-10-93 - TD 20'. Moving in rotary tools (United Drilling Rig #2).

Resumed drilling a 17-1/2" hole at 8:45 PM 8-10-93. Set 10' of 13-3/8" conductor. Cemented to surface. WOC 5 hours. Resumed drilling a 12-1/4" hole at 2:00 AM 8-11-93. Drilled to 452'. Ran 10 joints of 8-5/8" 24# J-55 (452') of casing set at 452'. 1-Texas Pattern Notched guide shoe set at 452'. Insert float set at 408'. Cemented with 150 sacks Class "C" 2% CaCl2 and 1/4#/sack celloseal (yield 1.32, weight 14.8). Tailed in with 100 sacks Class "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 4:00 PM 8-11-93. Bumped plug to 400 psi, OK. Circulated 75 sacks. WOC. Drilled out at 4:00 AM 8-12-93. WOC 12 hours. Nippled up and tested to 600# for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling.

NOTE: Notified NMOCD - Artesia of casing - no witness.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE August 19, 1993

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE AUG 27 1993

CONDITIONS OF APPROVAL, IF ANY: