

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-62976
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-233
7. Lease Name or Unit Agreement Name Carl ANO State
8. Well No. 4
9. Pool name or Wildcat Acme San Andres, Southeast

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS")

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter M : 330 Feet From The South Line and 990 Feet From The West Line
Section 1 Township 8S Range 27E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3967' GR

RECEIVED
JUL 31 1995
OIL CON. DIV.
DIST. 2

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <u>Frac perforations</u> <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-26-95 - Moved in and rigged up pulling unit. Loaded tubing with 2% KCL water. Nipped down wellhead and installed BOP. Unset packer. Dropped down and tagged PBTD at 2188'. TOOH with tubing and packer. Shut down.

7-27-95 - Removed BOP and nipped up frac head. Frac'd perforations 2151-2174' (San Andres) with 74000 gallons 30# crosslink gel and 240000# 20-40 Brady sand. Opened well at 1/2 BPM for forced closure. Shut well in.

7-28-95 - Bled well down to pit. Removed frac head and installed BOP. TIH with 2-7/8" tubing and tagged sand at 2149'. Reversed casing clean to 2191'. TOOH with tubing. Released well to production department.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE July 28, 1995

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY TIM W. GUM TITLE DISTRICT II SUPERVISOR DATE AUG 1 1995

CONDITIONS OF APPROVAL, IF ANY: