

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED

OCT 15 1993

WELL API NO.

30-005-62978

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

V-2925

7. Lease Name or Unit Agreement Name

Trailblazer ANL State

8. Well No.

2

9. Pool name or Wildcat

Southeast Acme San Andres

SUNDRY NOTICES AND REPORTS ON WELLS C. & D.
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter H : 2310 Feet From The North Line and 330 Feet From The East Line

Section 11

Township

8S

Range 27E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3969' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud, surface casing & cement ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole at 8:30 AM 8-19-93. Reached TD to run surface casing at 6:30 PM 8-19-93.

TD 473'. Ran 11 joints of 8-5/8" 24# J-55 (463.41') of casing set at 470.41'. 1-Texas Pattern notched guide shoe set at 470.41'. Insert float set at 426.21'. Cemented with 150 sacks Class "C", 2% CaCl2 and 1/4#/sack celloseal (yield 1.33, weight 14.8). Tailed in with 100 sacks Class "C" 2% CaCl2 (yield 1.33, weight 14.8). PD 9:50 PM 8-19-93. Bumped plug to 650 psi, OK. Circulated 63 sacks. WOC. Drilled out at 10:30 AM 8-20-93. WOC 12 hours and 40 minutes. Cut off and welded on flow nipple. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Production Clerk

DATE 10-13-93

TYPE OR PRINT NAME

Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS
SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

OCT 29 1993

CONDITIONS OF APPROVAL, IF ANY: