

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

clsf
op

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-62986

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Kilgore SO

8. Well No.
3

9. Pool name or Wildcat
Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Well Location
Unit Letter K : 2310 Feet From The South Line and 1980 Feet From The West Line

Section 24 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3799' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4300'. Reached TD 10-30-93. Ran 96 joints 4-1/2" 10.5# J-55 ST&C casing set 4299'. Regular guide shoe set 4299', float collar set 4252'. Cemented with 1000 gals Mud flush + 350 sx "C" with 17# CSE + 5% salt + 5# Hyseal + 3/10% CFR-2 (yield 1.76, wt 12.6). PD 6:45 PM 10-31-93. Bumped plug to 1300 psi, float held OK. WOC 18 hours. Ran 1" into 4-1/2" x 13-3/8" annulus to 1580'. Cemented with 550 sx PSL "C". Circulated cement to surface. TOH with 1" tubing. Perforated 3768-3920' w/15 - .48" holes as follows: 3768, 70, 91, 95, 97, 3801, 03, 05, 10, 3907, 11, 13, 15, 19 and 3920'. Straddled perforations 3907-20' and acidized with 1000 gals 7 1/2% NEFE acid. Straddled perforations 3768-3810' and acidized with 1000 gals 7 1/2% NEFE acid. Frac'd perforations 3768-3920' with 100000 gals 30# linear gel and 200000# 20/40 Brady sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Production Supervisor

DATE 11-8-93

TYPE OR PRINT NAME Juanita Goodlett

TELEPHONE NO. 505/748-147

(This space for State Use)

ORIGINAL SIGNED BY

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NOV 26 1993