

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

NOV 19 1993

WELL API NO.

30-005-62987

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Well Location

Unit Letter G : 2310 Feet From The North Line and 2310 Feet From The East Line

Section 35 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3716' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Production Casing, Perforate, Treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4200'. Reached TD 11-12-93. Ran 95 joints 4-1/2" 10.5# J-55 ST&C casing set 4200'. Regular guide shoe set 4200', float collar set 4152'. Cemented with 1000 gals mud flush + 350 sx Super "C" with 17# CSE + 5#/salt + 3/10% CF2 + 5# Hyseal (yield 1.73, wt 13.6). PD 4:00 PM 11-13-93. Bumped plug to 1500 psi for 3 minutes. WOC 18 hours. Ran 1" into 4 1/2" x 13-3/8" annulus to 1550'. Pumped 700 sx PSL "C" cement. Circulated cement to surface. TOH with 1" tubing. Perforated 3613-3806' w/15 - .42" holes as follows: 3613, 14, 15, 16, 17, 18, 19, 20, 3800, 01, 02, 03, 04, 05, and 3806'. Acidized perforations 3800-3806' w/500 gals. 7 1/2% NEFE acid. Acidized perforations 3613-3620' w/500 gals 7 1/2% NEFE acid. Frac'd down 4-1/2" casing perforations 3613-3806' w/40000 gals of 30# Linear gel + 80000# 20/40 Brady sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Production Supervisor

DATE 11-18-93

TYPE OR PRINT NAME

Juanita Goodlett

TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

SUPERVISOR DISTRICT II

TITLE

DATE

DEC 10 1993

CONDITIONS OF APPROVAL, IF ANY: