

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

OCT 18 1993

WELL API NO.	30-005-62970
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-3093

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name Jacci State
2. Name of Operator United Drilling, Inc.	8. Well No. 1
3. Address of Operator P.O. Box 2488, Roswell, NM 88202	9. Pool name or Wildcat Wolf Lake - San Andres
4. Well Location Unit Letter I : 1650 Feet From The South Line and 990 Feet From The East Section 36 Township 8S Range 27E NMPM Chaves County	10. Elevation (Show whether DF, RKB, KT, GR, etc.) 3912 G.L.

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 12-1/4 hole to 400 ft., set 400 ft. 8-5/8" , 24# casing. Circulated cement to surface. Wait on cement.

Drill 7-7/8" hole to 2354 ft. Logged well. No production casing run.

Plugged well as follows: 30 sacks at 1680' (October 26, 1993)
30 sacks at 1280'
30 sacks at 1000'
30 sacks at 450' - Tagged
60' of cement at surface
Dry hole marker set.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Angel Salazar TITLE Vice President DATE 10-26-93

TYPE OR PRINT NAME Angel Salazar

TELEPHONE NO. 623-7730

(This space for State Use)

APPROVED BY SUPERVISOR, DISTRICT II TITLE DATE DEC 29 1993