

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-005-63005
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2924
7. Lease Name or Unit Agreement Name J. Horton State
8. Well No. 1
9. Pool name or Wildcat SE Acme San-Andres Pool

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator  
Collins Oil & Gas Corporation

3. Address of Operator  
P.O. Box 2443, Roswell, NM 88202-2443

4. Well Location  
Unit Letter P : 330 Feet From The South Line and 330 Feet From The East Line

Section 2 Township 8-S Range 27E NMPM Chaves County  
10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3955 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-3-94 Ran 433' of 8-5/8", 24 lb. J-55 casing with insert float and Texas Pattern guide shoe. Pumped 233 sxs. of Class "C" cement with 2% CaCl. Approximately 55 sxs. circulated to pits.

3-4-94 Drying time on cement was approximately 18 hours. Pressure tested casing to 650 lbs., no droppage of pressure in 30 minutes. Resumed drilling operations.

3-7-94 T.D. hole at 2199'.

3-8-94 Ran 2199' of 4 1/2", J-55, 10.50 lb. casing with insert float & guide shoe. Pumped 275 sxs. of Class "C" cement with 2% CaCl.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roy D. Collins TITLE Pres. Collins O/G DATE 3-9-94

TYPE OR PRINT NAME ROY D. COLLINS TELEPHONE NO. 623-2040

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE APR 8 1994

CONDITIONS OF APPROVAL, IF ANY:

