

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-005-63009

Operator <u>Yates Petroleum Corp</u>		Lease <u>Barclay "ALM" Com</u>		Well # <u>1</u>	
Location of Well	Unit <u>F</u>	Section <u>33</u>	Township <u>6</u>	Range <u>26</u>	County <u>Chaves</u>
Drilling Contractor	<u>NA</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14.75</u>	<u>* 9.625</u>	<u>36 #</u>		<u>900</u>	<u>750 Circ</u>
<u>7.875</u>	<u>4.5</u>	<u>10.5 #</u>		<u>TD 4300</u>	<u>350 As</u>
					<u>warranted</u>

Casing Data:

Surface 20 joints of 9 5/8 inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by Joedate 7/1/94

Cementing Program

Size of hole 14 3/4 Size of Casing 9 5/8 Sacks cement required 750 sxsType of Shoe used Guide Float collar used Insert Btm 3 jts welded YesTD of hole 899 Set 905 Feet of 9 5/8 Inch 36 # Grade J-55New used csg. @ 500 sxs with 200 sxs sacks neat cement around shoe+ sax additives 2 1/2 ccPlug down @ 3:30 (AM) (PM) Date 7/3/94Cement circulated Yes No. of Sacks 120 sxs to PitCemented by Western + Co. Witnessed by Joe WellsTemp. Survey ran @ (AM) (PM) Date top cement @ Casing test @ (AM) (PM) Date Method Used Witnessed by Checked for shut off @ (AM) (PM) Date Method used Witnessed by Remarks: