

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Submit 3 Copies
to Appropriate
District Office

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-005-63009

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Barclay ALM Com

8. Well No.

1

9. Pool name or Wildcat

Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter F : 1980 Feet From The North Line and 1980 Feet From The West Line

Section 33

Township 6S

Range 26E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3601' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud, Resume drilling, surface casing and cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole digger at 5:15 PM 6-28-94. Set 40' of 20" conductor pipe. Cemented with 75 sacks Class "C" Neat cement. NOTE: Notified Betty with the OCD in Artesia. of spud. Resumed drilling a 14-3/4" hole with rotary tools at 6:45 AM 7-1-94.

TD 899'. Reached TD at 4:30 PM 7-2-94. Ran 20 joints of 9-5/8" 36# J-55 (901.88') of casing set at 899'. 1-Texas Pattern notched guide shoe set at 899'. Davis Lynch insert float set at 856'. Cemented with 500 sacks Pacesetter Lite "C", 10#/sack gilsonite, 1/4# / sack celloseal and 3% CaCl2 (yield 1.98, weight 12.4). Tailed in with 200 sacks Class "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 3:30 AM 7-3-94. Bumped plug to 750 psi, OK. Circulated 120 sacks cement. WOC. Drilled out at 1:45 AM 7-4-94. WOC 22 hours and 15 minutes. Cut off and welded on flow nipple. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE Production Clerk

DATE July 6, 1994

TYPE OR PRINT NAME

Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

JUL 29 1994