

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-005-63010

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

7. Lease Name or Unit Agreement Name

Hancock AHC Com

8. Well No.

3

9. Pool name or Wildcat

Pecos Slope Abo

4. Well Location

Unit Letter 0 : 660 Feet From The South Line and 1980 Feet From The East Line

Section 20 Township 6S Range 26E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3627' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

OTHER: Resume drilling, surface casing & cmt

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 14-3/4" hole at 5:00 PM 11-23-94. Drilled to 503'. Reduced hole to 12-1/4". Reached TD of 12-1/4" hole at 2:30 PM 11-25-94. Ran 21 joints of 9-5/8" 36# J-55 (933.75') of casing set at 935'. 1-Texas Pattern notched guide shoe set at 935'. Insert float set at 891'. Cemented with 200 sacks "H", 12% Thixad, 2% CaCl2, 10#/sack gilsonite and 1/2#/sack celloseal (yield 1.57, weight 14.6). Tailed in with 500 sacks Pacesetter Lite "C", 3% CaCl2 and 1/4#/sack celloseal (yield 1.99, weight 12.5) and 250 sacks C 2% CaCl2 (yield 1.32, weight 14.8). PD 8:38 PM 11-25-94. Bumped plug to 900 psi, OK. Circulated 240 sacks. WOC. Drilled out at 3:00 PM 11-26-94. WOC 18 hours and 38 minutes. Cut off and weld on flow nipple. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Production Clerk

DATE 12-2-94

TYPE OR PRINT NAME

Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use)

SUPERVISOR, DISTRICT II

DEC 19 1994

DATE