

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89
d/sr
dp

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-005-63015
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. L-6274
7. Lease Name or Unit Agreement Name Dee OQ State
8. Well No. 5
9. Pool name or Wildcat Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

1. Type of Well: OIL WELL GAS WELL OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South Fourth Street - Artesia, NM 88210

AUG 16 '94

O. C. D.
ARTESIA, OFFICE

4. Well Location
Unit Letter K : 2310 Feet From The South Line and 2310 Feet From The West Line
Section 32 Township 5S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3779' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: _____ <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, resume drilling, surface casing and cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 10:00 AM 8-7-94. Set 40' of 20" conductor pipe. Cemented with 3 yards of Ready-Mix. NOTE: Notified Gary with OCD prior to spud. Resumed drilling a 14-3/4" hole with rotary tools at 1:00 PM 8-9-94. Drilled a 14-3/4" hole to 558' and reduced hole to 12-1/4". Drilled 12-1/4" hole to 900'. Reached TD of 12-1/4" hole at 10:30 PM 8-10-94. Ran 20 joints of 9-5/8" 36# J-55 (902.47') of casing set at 900'. 1-Texas Pattern notched guide shoe set at 900'. Insert float set at 853.74'. Cemented with 500 sacks Pacesetter Lite, 1/4#/sack celloseal and 3% CaCl2 (yield 1.98, weight 12.5). Tailed in with 250 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 4:30 AM 8-11-94. Bumped plug to 700 psi, OK. Circulated 150 sacks. WOC. NOTE: Notified OCD prior to job. Drilled out at 10:30 PM 8-11-94. WOC 18 hours. Nipped up and tested to 1000 psi for 30 minutes. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 8-15-94

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505-748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE SEP 6 1994