

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-005-63016

Operator <u>Gates Petr Corp</u>		Lease <u>Crandall "UD"</u>		Well # <u>2</u>	
Location of Well	Unit <u>B</u>	Section <u>6</u>	Township <u>7</u>	Range <u>26</u>	County <u>Chaves</u>
Drilling Contractor	<u>NA</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14.75</u>	* <u>9.625</u>	<u>36</u>		<u>900</u>	<u>700 Circ</u>
<u>8.75</u>	<u>7.0</u>	<u>23</u>		<u>1500</u>	<u>250</u>
<u>7.875</u>	<u>4.5</u>	<u>10.5</u>		<u>TD</u>	<u>350</u>

Casing Data:

Surface _____ joints of 9 5/8 inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. date Oct. 25-94

Cementing Program

Size of hole 12.25 Size of Casing 9 5/8" Sacks cement required _____

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 932' Set 932' Feet of 9 5/8" Inch 36 # Grade J-55

(New) used csg. @ 932' with 250 220cc sacks neat cement around shoe

+ 500 sax Pacesetter Lite additives 1/4" closed, 320cc

Plug down @ 5:45 (AM) (PM) Date Oct. 27-94

Cement circulated yes No. of Sacks 200

Cemented by Western Company Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

12 1/4" hole RT. was 25 hours. L.D.B. - 820'