

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30-005-63016

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Crandall UD

8. Well No.

2

9. Pool name or Wildcat

Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT, MINERAL OFFICE (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL WELL ☐

GAS WELL ☒

OTHER ☐

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter B : 510 Feet From The North Line and 1980 Feet From The East Line

Section 6

Township 7S

Range 26E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3659' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

OTHER: Surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 932'. Ran 21 joints of 9-5/8" 36# J-55 (936.50') of casing set at 932'. 1-Texas Pattern notched guide shoe set at 932'. Insert float set at 887'. Cemented with 500 sacks Pacesetter Lite "C", 1/4#/sack celloseal and 2% CaCl2 (yield 1.99, weight 12.4). Tailed in with 250 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 5:40 AM 10-27-94. Bumped plug to 750 psi, OK. Circulated 200 sacks. WOC. Drilled out at 3:00 PM 10-28-94. WOC 21 hours and 20 minutes. Cut off and weld on flow nipple. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Production Clerk

DATE 10-31-94

TYPE OR PRINT NAME

Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

NOV 21 1994