June 1990) DEPARTMEN BUREAU OF I SUNDRY NOTICES Do not use this form for proposals to dr	AD STATES Drawer T OF THE INTERIOR tesi LAND MANAGEMENT	SEEEVEED	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. <u>NM-28162</u> 6. If Indian, Allottee or Tribe Name
SUBMIT	IN TRIPLICATE	RECEIVED	7. If Unit or CA, Agreement Designation
 Type of Well Oil X Gas Well X Well Other Name of Operator YATES PETROLEUM CORPORATION Address and Telephone No 105 South 4th St., Artesia, Location of Well (Footage, Sec., T., R., M., or Survey D 990' FNL & 2310' FWL of Secti 	NM 88210 rescription)	C. C. D. ARTESIA, OFFICE	 8. Well Name and No. <u>Thorpe MI Federal #15</u> 9. API Well No. <u>30-005-63020</u> 10. Field and Pool, or Exploratory Area <u>Pecos Slope Abo</u> 11. County or Parish, State Chaves Co., NM
12. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE	OF NOTICE, REPOF	RT, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	Change of Plans
E Subsequent Report	Recompletion Plugging Back Casing Repair Altering Casing Other Resum	ne drilling, surfa	Non-Routine Fracturing Water Shut-Off Conversion to Injection
13. Describe Proposed or Completed Operations (Clearly state	casir	ng & cement	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drifted, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
Resumed drilling a 17-1/2" hole at 5:30 PM 9-9-94.

TD 873'. Reached TD at 12:01 AM 9-13-94. Ran 21 joints of 13-3/8" 54.5# J-55 (880.17') of casing set at 873'. 1-Texas Pattern notched guide shoe set at 873'. Insert float set at 830'. Cemented with 500 sacks Pacesetter Lite C, 1/4#/sack celloseal and 3% CaCl2 (yield 1.98, weight 12.5). Tailed in with 250 sacks "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 6:56 AM 9-13-94. Bumped plug to 600 psi, OK. Circulated 170 sacks. WOC. Drilled out at 1:15 AM 9-14-94. WOC 18 hours and 20 minutes. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Resumed drilling.

4. I hereby certify that the foregoing is use and correct Signed Huster Hult		n Clerk
(This space for Federal of State office use)		HELER WEIGHT
Approved by Conditions of approval, if any:	Title	SEP 2 6 1394
itle 18 U.S.C. Section 1001, makes it a crime for any perso representations as to any matter within its jurisdiction.	n knowingly and willfully to make to any de	partment or aggncy of the United States any false, fictitious or fraudulent stateme