

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Drawer DD

Artesia

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

Lease Designation and Serial No.

NM-32167

6. Indian, Allottee or Tribe Name

If Unit or CA, Agreement Designation

SUNDRY NOTICES AND REPORTS ON WELL

Do not use this form for proposals to drill or to deepen or reentry of a different well.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

Address and Telephone No.

105 South 4th St., Artesia, NM 88210

Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL & 1980' FEL of Section 5-T6S-R26E (Unit B, NWNE)

8. Well Name and No.

Spring Federal #4

9. API Well No.

30-005-63022

10. Field and Pool, or Exploratory Area

C. Dejos Slope Abo

11. County or Parish, State

Chaves Co., NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Resume drilling, surface casing & cement  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water  
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

3. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Resumed drilling a 12-1/4" hole with rotary tools at 3:30 PM 10-14-94.

TD 935'. Reached TD at 6:30 AM 10-16-94. Ran 21 joints of 9-5/8" 36# J-55 (938.66') of casing set at 935'. 1-Texas Pattern notched guide shoe set at 935'. Insert float set at 891'. Cemented with 550 sacks Pacesetter Lite C, 10#/sack gilsonite, 1/4#/sack celloseal and 3% CaCl2 (yield 1.99, weight 12.5). Tailed in with 250 sacks "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 12:30 PM 10-16-94. Bumped plug to 700 psi, OK. Circulated 180 sacks. WOC. Drilled out at 6:30 AM 10-17-94. WOC 18 hours. Cut off and weld on flow nipple. Reduced hole to 8-3/4". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed Rusty Klein Title Production Clerk

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Date Oct. 27, 1994

ACCEPTED FOR RECORD  
PETER W. CHESTER  
Date

NOV 1 1994

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side