

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-63036
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2982
7. Lease Name or Unit Agreement Name Quincy AMQ State
8. Well No. 6
9. Pool name or Wildcat Acme San Andres Southeast
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3947' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter F : 2310 Feet From The North Line and 1650 Feet From The West Line Section 12 Township 8S Range 27E NMPM Chaves County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole with rotary tools at 8:00 AM 2-8-95.

TD 475'. Reached TD at 7:00 PM 2-9-95. Ran 11 joints of 8-5/8" 24# J-55 (471.04') of casing set at 464'. 1-Texas Pattern notched guide shoe set at 464'. Insert float set at 417'. Cemented with 150 sacks Class C, 2% CaCl₂ and 1/4#/sack celloseal (yield 1.33, weight 14.8). Tailed in with 100 sacks Class C Neat with 2% CaCl₂ (yield 1.33, weight 14.8). PD 11:20 AM 2-10-95. Bumped plug to 750 psi, float did not hold. Circulated 126 sacks to pit. WOC. Drilled out at 10:00 AM 2-11-95. WOC 23 hours and 20 minutes. Cut off and weld on flow nipple. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 2-17-95
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

FEB 27 1995

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: