

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-63037
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2982
7. Lease Name or Unit Agreement Name Quincy AMO, State
8. Well No. 5
9. Pool name or Wildcat Southeast Acme San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3968' GR

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter E : 1650 Feet From The North Line and 990 Feet From The West Line Section 12 Township 8S Range 27E NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3968' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: spud, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 12:00 PM 1-18-95. Set 5' of 13-3/8" conductor pipe. Filled hole with ready-mix. NOTE: Notified OCD - Artesia of spud. Reduced hole to 12-1/4".

TD 447'. Reached TD at 6:30 AM 1-19-95. Ran and landed 10 joints of 8-5/8" 24# 8rd ST&C J-55 (438.51') of casing landed at 447' with 14.60' landing joint. 1-Texas Pattern notched guide shoe set at 447'. Insert float set at 408'. Cemented with 150 sacks "C", 1/4#/sack celloseal and 2% CaCl2 (yield 1.32, weight 14.8). Tailed in with 100 sacks "C" with 2% CaCl2 (yield 1.32, weight 14.8). PD 9:45 AM 1-19-95. Bumped plug to 600 psi, OK. Circulated 120 sacks to pit. WOC. Drilled out at 9:45 PM 1-19-95. WOC 12 hours. Backed out landing joint. Nipped up rotating head. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 1-24-95  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

**ORIGINAL SIGNED BY TIM W. GUM**  
**DISTRICT II SUPERVISOR**

**FEB 9 1995**

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: