

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-63037
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-8902
7. Lease Name or Unit Agreement Name Quincy AMQ State
8. Well No. E-8902
9. Pool name or Wildcat Southeast Acme San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3968' GR

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter <u>E</u> : <u>1650</u> Feet From The <u>North</u> Line and <u>990</u> Feet From The <u>West</u> Line Section <u>12</u> Township <u>8S</u> Range <u>27E</u> NMPM <u>Chaves</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3968' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>Production casing &amp; cement</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2218'. Ran 56 joints of 5-1/2" 17# J-55 8rd LT&C (2224.62') of casing set at 2218'. 1-regular guide shoe set at 2218'. Float collar set at 2213'. Cemented with 40 sacks of salt water gel and 300 sacks "C" and 1/2% CF-14 (yield 1.32, weight 14.8). PD 10:15 PM 1-23-95. Bumped plug to 1250 psi for 3 minutes. Released rig at 11:15 PM 1-24-95.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 1-24-95  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY THE W. GUM  
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

FEB 9 1995

CONDITIONS OF APPROVAL, IF ANY: