		~			d
				Cons. L. Isior	n Cl
			811 S. 1st S		
rm 3160-5 ine 1990)	DEPARTMEN	TED STATES	R	88210-2834	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993
	BUREAU OF	LAND MANAGEME	NT	5	. Lease Designation and Serial No.
S	UNDRY NOTICES	AND REPORTS OF	N WELLS		NM-54991
Do not use this form Use	n for proposals to di HAPPLICATION FO	rill or to deepen or re R PERMIT'' for suc	entry to a different	ont reservoir.	. If Indian, Allottee or Tribe Name
······································	SUBMIT	IN TRIPLICATE	in an	7	. If Unit or CA, Agreement Designation
Type of Well Oil Well X Well	Other		<u>.</u>	<u>7 1 5 2 2 8 .</u>	Well Name and No.
Name of Operator		1		G	etty PS 18 Fed Com #3
	UM CORPORATION	V (50	)5) 748-1471)	9.	API Well No.
Address and Telephone No.	St Artoolo	NM 99210			30-005-63049
	St., Artesia, Sec., T., R., M., or Survey D			10	Field and Pool, or Exploratory Area
		tion 18-T65-R26	Gunit I M	1971) 11	Pecos Slope Abo . County or Parish, State
1900 100 4 1		100 100 K20	- (onre 5, M	13E)	
	· · · · ·				Chaves Co., NM
CHECK AP	PROPRIATE BOX	(s) TO INDICATE N	ATURE OF NO	TICE. REPORT.	
TYPE OF SU				PE OF ACTION	
	leni		donment		
	iicin		mpletion		Change of Plans New Construction
X Subsequent Report					
X Subsequent	Report	Plug	ging Back		Non-Routine Fracturing
X Subsequent	Report		ging Back ng Repair		Non-Routine Fracturing Water Shut-Off
Ē	Report Ionment Notice		ng Repair ing Casing		
Ē			ng Repair		Water Shut-Off Conversion to Injection Dispose Water
Final Aband	Ionment Notice	Casi Alter X Othe	ng Repair ing Casing r Production	······································	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Final Aband	ionment Notice eted Operations (Clearly state a	Casi Alter X Othe	ing Repair ing Casing r Production (	mated date of starting any	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with	tend Operations (Clearly state a s and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9-	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with	tend Operations (Clearly state a as and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a	tend Operations (Clearly state a as and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a	tend Operations (Clearly state a as and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a	tend Operations (Clearly state a s and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a	tend Operations (Clearly state a s and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a	tend Operations (Clearly state a s and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a	tend Operations (Clearly state a s and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a	tend Operations (Clearly state a s and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a Waiting on com	tonment Notice eted Operations (Clearly state a as and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30 npletion unit.	Casi Alter X othe X othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)" (16.85'). 1 (allons mud f and 8#/sack si for 3 min	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a Waiting on com	tonment Notice eted Operations (Clearly state a as and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30 npletion unit.	Casi Alter X Othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint -96,	ng Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p at 3633-3646	mated date of starting any (k.)* (16.85'). 1 (allons mud f and 8#/sack si for 3 min ', sandblast	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Recompletion Report and Log form ) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE: ed casing 3520-4200'.
Final Aband Describe Proposed or Comple- give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a Waiting on com	tend Operations (Clearly state a ss and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30 npletion unit.	Casi Alter X Othe It pertinent details, and give pert cal depths for all markers and x M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint -96,	ing Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p	mated date of starting any (k.)* (16.85'). 1 (allons mud f and 8#/sack si for 3 min ', sandblast	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE:
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a Waiting on com	tered Operations (Clearly state a ss and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30 npletion unit.	Casi Alter X Othe Il pertinent details, and give pert cal depths for all markers and is M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint -96, 	ng Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p at 3633-3646	mated date of starting any (k.)* (16.85'). 1 (allons mud f and 8#/sack si for 3 min ', sandblast	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Recompletion Report and Log form ) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE: ed casing 3520-4200'.
Final Aband Describe Proposed or Comple give subsurface location TD 4204'. Rea (4186.47') of set at 4200'. sacks Super Mo weight 13.0). Displaced with Released rig a Waiting on com	tered Operations (Clearly state a ss and measured and true verti ached TD 1:45 Al casing landed Float collar odified C, 3.28 PD 5:45 AM 9- n 2% Clay Treat at 9:45 AM 9-30 npletion unit.	Casi Alter X Othe Il pertinent details, and give pert cal depths for all markers and a M 9-29-96. Ran at 4200' with 1a set at 4158'. F #/sack salt, .31 30-96. Bumped p . Marker joint -96,	ng Repair ing Casing Production of inent dates, including esti- ones pertinent to this wo 100 joints of nding joint umped 1000 g #/sack FL52 lug to 500 p at 3633-3646	mated date of starting any (k.)* (16.85'). 1 (allons mud f and 8#/sack si for 3 min ', sandblast	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Recompletion Report and Log form ) proposed work. If well is directionally drille 5# 8rd J-55 ST&C -regular guide shoe lush ahead of 350 gilsonite (yield 1.68, utes. WOC. NOTE: ed casing 3520-4200'.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. \_\_\_\_\_