

Submit 3 Copies
to Appropriate
District Office

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-005-63050
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-2982
7. Lease Name or Unit Agreement Name	
Quincy AMQ State	
8. Well No.	7
9. Pool name or Wildcat	
Acme San Andres, Southeast	
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
3956' GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator
YATES PETROLEUM CORPORATION
3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter F : 1650 Feet From The North Line and 1650 Feet From The West Line
Section 12 Township 8S Range 27E NMPM Chaves County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2220'. Reached TD at 3:00 PM 3-15-95! Ran 52 joints of 5-1/2" 15.5# J-55 8rd LT&C (2225') of casing set at 2225'. 1-regular guide shoe set at 2220'. Float collar set at 2215'. Cemented with 350 sacks Class C and .5% CF-14 (yield 1.32, weight 14.8). PD 1:30 PM 3-16-95. Bumped plug to 1400 psi for 5 minutes, OK. Cement circulated 20 sacks. Released rig at 4:00 PM 3-16-95. NOTE: Sandblasted pipe across pay. Centralizers set at on joints #1, 3, 5, 7 & 9.

Waiting on completion unit.

RECEIVED

MAR 20 1995

OIL CON. DIV.
DIST. 2

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 3-17-95

TYPE OR PRINT NAME Rusty Klein

TELEPHONE NO. 505/748-147

(This space for State Use)

ORIGINAL SIGNED BY TWA M. GUM
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

MAR 20 1995

CONDITIONS OF APPROVAL, IF ANY: