

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1750' FNL & 660' FWL of Section 15-T7S-R25E (Unit E, SWNW)

5. Lease Designation and Serial No.

NM-28162

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Thorpe MI Federal Com #14

9. API Well No.

30-005-63058

10. Field and Pool, or Exploratory Area

Pecos Slope Abo

11. County or Parish, State

Chaves Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud & conductor,
surface casing & cement

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 20" hole with rat hole machine at 12:15 PM 2-17-97. Set 40' of 16" conductor pipe. Cemented to surface. Resumed drilling a 14-3/4" hole with rotary tools at 7:00 PM 2-27-97.

TD 805'. Reached TD at 7:15 AM 3-1-97. Ran 19 joints of 11-3/4" 42# H40 8rd ST&C (806.61') of casing set at 805'. 1-Texas Pattern notched guide shoe set at 805'. Insert float set at 763'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 400 sacks Poz (65-35-6), 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.7). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 3:00 PM 3-1-97. Bumped plug to 500 psi, OK. Circulated 275 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 3:15 AM 3-2-97. WOC 12 hours and 15 minutes. Reduced hole to 11". Resumed drilling.

RECEIVED FOR RECORD
PETER W. CHESTER

MAR 11 1997

RECEIVED

MAR 10 97

14. I hereby certify that the foregoing is true and correct

Signed

Rusty Klein

Title

Operations Technician

Date

March 6, 1997

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date