

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-63059
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2982
7. Lease Name or Unit Agreement Name Quincy AMQ State
8. Well No. 14
9. Pool name or Wildcat Acme San Andres, Southeast

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter N : 990 Feet From The South Line and 2310 Feet From The West Line Section 12 Township 8S Range 27E NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3939' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER: <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: Spud, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole with rotary tools at 7:30 AM 7-31-95.

TD 470'. Reached TD at 6:45 PM 7-31-95. Ran 10 joints of 8-5/8" 24# J-55 8rd (458') of casing landed at 470'. 1-Texas Pattern notched guide shoe set at 470'. Cemented with 150 sacks "C", 1/4#/sack celloseal and 2% CaCl2 (yield 1.32, weight 14.8). Tailed in with 100 sacks "C" 2% CaCl2 (yield 1.32, weight 14.8). PD 11:15 PM 7-31-95. Bumped plug to 600 psi, float did not hold. Drilled out at 1:00 PM 8-1-95. WOC 13 hours and 45 minutes. Nippled up and tested to 1000# for 30 minutes, OK. Reduced hole to 7-7/8". Resumed drilling. NOTE: Weld shoe and 3 joints. Centralizers on joints #1, #3, #5 and #7. Pumped 15 bags gelled water ahead of cement.

OIL CON. DIV.
DIST. 2

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE Aug. 7, 1995
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

AUG 10 1995