Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103	/
Revised 1-1-89	L

DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION

DISTRICT II P.O. Drawer DD, Artesia, NM 88210 P.O. Box 2088 Santa Fe, New Mexico 87504-2088 WELL API NO. 30-005-63078

5. Indicate Type of Lease S

STATE FEE

DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410	6. State Oil & Gas Lease No.	
· · · · · · · · · · · · · · · · · · ·	V-2982	
SUNDRY NOTICES AND REPORTS ON WELLS	HO BACK TO A	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PI DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"	7. Lease Name or Unit Agreement Name	
(FORM C-101) FOR SUCH PROPOSALS		
1. Type of Well:		
OR. WELL OTHER	Quincy AMQ State	
YATES PETROLEUM CORPORATION	27 1997 8. Well No.	
3. Address of Operator	ON DIV. Pool name or Wildcat Acme. San. Andres. Southeast	
	Acine San Andres, Southeast	
Unit Letter N: 330 Feet From The South	MST. 2	
Unit Letter; Feet From The	Line and 1650 Feet From The West Line	
Section 12 Township 8S Range	27E NMPM Chaves County	
10. Elevation (Show whether DF, RK	B, RT, GR, etc.)	
//////////////////////////////////////		
11. Check Appropriate Box to Indicate Natur	e of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REM	BEDIAL WORK ALTERING CASING	
TEMPORARILY ABANDON CHANGE PLANS CON	IMENCE DRILLING OPNS. PLUG AND ABANDONMENT	
PULL OR ALTER CASING CAS	CASING TEST AND CEMENT JOB	
OTHER: OTH	ER Resume drilling, surface casing & cmt X	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed		
work) SEE RULE 1103. Resumed drilling a 12-1/4" hole with rotary too.	Is at 9:00 PM 3-18-97.	
Resulted diffiling a 12 1/4 hore with foraty coo.	10 de 7,00 III 3 10 77.	
TD 373'. Reached TD at 11:15 AM 3-19-97. Ran	11 joints of 8-5/8" 24# J-55 8rd ST&C	
(471.94') of casing set at 469'. 1-Texas Pattern notched guide shoe set at 469'.		
Insert float set at 427'. Cemented with 300 sacks "C" and 2% CaCl2 (yield 1.32, weight		
14.8). PD 5:15 PM 3-19-97. Bumped plug to 900 psi, OK. Circulated 51 sacks. WOC.		
Nippled up and tested to 1000# for 30 minutes,		
WOC 12 hours. Reduced hole to 7-7/8". Resumed	drilling.	
ma ²		
\mathcal{W} .		
I hereby certify that the information above is true-and complete to the best of my knowledge and belief.		
SIGNATURE Kustys Title 0	perations Technician pare March 25, 1997	
Puote Viota	E05/7/0 1/	

(This space for State Use) RIG!MAL SIGNED BY TIM W. GUM

TELEPHONE NO. 505/748-1471

DISTRICT II SUPERVISOR TILE MAR 3 1 1997

APPROVED BY-