

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-005-63079

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-2982

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter N : 330 Feet From The South Line and 2310 Feet From The West Line
Section 12 Township 8S Range 27E NMPM Chaves County

5. Lease Name or Unit Agreement Name
Quincy AMO State

6. Well No.
17

7. Pool Name or Wildcat
Acme San Andres, Southeast

8. Elevation (Show whether DF, RKB, RT, GR, etc.)
3939' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Spud, surface casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rotary tools at 10:45 AM 4-1-97. Set 10' of 16" conductor pipe. Cemented to surface. NOTE: Notified Betty Rollins w/OCD-Artesia of spud.

TD 475'. Reached TD of 12-1/4" hole at 10:30 PM 4-1-97. Ran 11 joints of 8-5/8" 24# J-55 8rd ST&C (471.73') of casing set at 468'. 1-Texas Pattern notched guide shoe set at 468'. Insert float set at 426'. Cemented with 300 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 1:30 AM 4-2-97. Bumped plug to 750 psi, OK. Circulated 150 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes. Drilled out at 3:00 PM 4-2-97. WOC 13-1/2 hours. Reduced hole to 7-7/8". Resumed drilling.

WOC = 18 hrs
Reg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 4, 1997

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APR 9 1997

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: