

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FNL & 990' FEL of Section 15-T6S-R25E (Unit A, NENE)

5. Lease Designation and Serial No.

NM-14755

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Powers OL Federal Com #13

9. API Well No.

30-005-63096

10. Field and Pool, or Exploratory Area

Pecos Slope Abo

11. County or Parish, State

Chaves Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Resume drilling, surface casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Resumed drilling a 14-3/4" hole with rotary tools at 9:00 PM 3-9-97.

TD 900'. Reached TD at 11:45 AM 3-11-97. Ran 22 joints of 11-3/4" 42# H40 8rd ST&C (900.74') of casing set at 900'. 1-Texas Pattern notched guide shoe set at 900'. Float collar set at 856'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks "C" 65-35-6, 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.7). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 6:00 PM 3-11-97. Did not bump plug. Circulated 176 sacks. WOC. TIH and tagged top of cement at 830'. NOTE: Notified Armando Lopez w/BLM-Roswell - no witness. Cut off and welded on flow nipple. Drilled out at 6:00 AM 3-12-97. WOC 12 hours. Reduced hole to 11" Resumed drilling.

ACCEPTED FOR RECORD
PETER W. CHESTER

MAR 20 1997

BUREAU OF LAND MANAGEMENT
ROS WELL RESOURCE AREA

RECEIVED

MAR 19 97

BLM
ROS WELL, NM
Date March 18, 1997

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date