Form 3160-5 (June 1990)

or representations as to any matter within its jurisdiction.

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

WELL	000	JIV I	NM - 10	263	
1.	COVE	If Median,	Allottee	or Tribe	Nan

Date .

Do not use this form for proposals to dr	III or to deepen or reentry to a difference of the PERMIT—" for such proposals 1995	1 Typdian, Allottee or Tribe Name 3(282) 7. If Unit or CA, Agreement Designation	
SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
1. Type of Well	28.05 C 38.05	7 × 2 0 //	
Oil X Gas Other	· · · · · · · · · · · · · · · · · · ·	8. Well Name and No.	
2. Name of Operator	1	Thomas LN Federal #8	
YATES PETROLEUM CORPORATION	9. API Well No.		
3. Address and Telephone No.	30-005-63097		
105 South 4th St., Artesia, 1	10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey D	Pecos Slope Abo		
1980' FNL & 1980' FWL of Sect	11. County or Parish, State		
		Chaves Co., NM	
CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION		
Notice of Intent	Abandonment	Change of Plans	
<u></u>	Recompletion	New Construction	
X Subsequent Report	Plugging Back	Non-Routine Fracturing	
	Casing Repair	Water Shut-Off	
Final Abandonment Notice	Altering Casing	Conversion to Injection	
	X Other Perforate & frac	Dispose Water (Note: Report results of multiple completion on Well	
give subsurface locations and measured and true vertice	Il pertinent details, and give pertinent dates, including estimated date of star cal depths for all markers and zones pertinent to this work.)*		
3-5-97 - Rigged up wireline.	TIH with logging tools and ran GR/	CCL/CBL log. TOOH with	
up wireline. TIH with 3-3/8	n wireline. Cleaned location, set a " casing guns and perforated 3546-35	nd tested anchor. Rigged 56' w/44 .38" holes.	
TOOH with casing guns and ri	gged down wireline.		
20# delayed crosslink borate	rac valve. Frac'd perforations 3546 gel and 240000# 16-30 Brady sand.	-3556' with 82350 gallons Tagged sand with IR-192.	
Tested to 1000 psi. TIH wit	up pulling unit. Nippled down frach seating nipple and 2-3/8" tubing.	Tagged sand at 3570'.	
Washed sand to 3800'. Circu	lated well clean. Pulled up to 3473	and set seating nipple.	
Nippled down BOP and nippled	up wellhead. Swabbing.		
3-8-97 - Continue to swab.	PETER WE SOR RECORD		
3-9-97 - Continue to swab. 3-10-97 - Swabbed. Released	well to production department.	PETER W. CHESTER	
		MAR 1 8 1997	
		BURFAL OF LAW	
		BURFAL OF LAND MANAGEMENT ROSWILL RESOURCE AREA	
14. I hereby certify that the foregoing is true and correct		REE AREA	
Signed Justin Tillen	Tide Operations Technician	Date March 13, 1997	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements