dsf

Form 3160-5 (June 1990)

UNITED STATES 11 TO THE INTERIOR AND THE INTERIOR BUREAU OF LAND MANAGEMENTALY 1 5 1997

FORM APPROVED
Attack 114 8 210 BiggerBureau No. 1004-0135
Expires: March 31, 1993

| | AND MANAGEMENTAY 15 1997 | 5. Lease Designation and Serial No. |
|---|---|---|
| SUNDRY NOTICES : Do not use this form for proposals to dri | | <u> </u> |
| SUBMIT | IN TRIPLICATE BUREAU OF LAN | 7. If Unit or CA, Agreement Designation |
| 1. Type of Well Oil Sas Other | ROSWELL OF | 8. Well Name and No. |
| 2. Name of Operator YATES PETROLEUM CORPORATION | (505) 748-1471) | Thomas LN Federal #9 9. API Well-No. |
| 3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210 | | 30-005-63099 10. Field and Pool, or Exploratory Area |
| 4 Location of Well (Footage, Sec., T., R., M., or Survey D. 2310 FSL & 1300 FWL of Sect | escription) tion 10-T6S-R25E (Unit L, NWSW) | Pecos Slope Abo 11. County or Parish, State |
| OUTON ADDDODDIATE DOV | (s) TO INDICATE NATURE OF NOTICE, REP | Chaves Co., NM |
| | TYPE OF ACTIO | |
| TYPE OF SUBMISSION | | Change of Plans |
| X Notice of Intent Subsequent Report | Abandonment Recompletion Plugging Back | New Construction Non-Routine Fracturing |
| Final Abandonment Notice | Casing Repair Altering Casing Other | Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form) |
| give subsurface locations and measured and true vertices as follows: FROM: 14-3/4" hole with 9-5/8" 36# 67-7/8" hole with 7" 20# casing 7-7/8" hole with 4-1/2" 10.5# TO: 14-3/4" hole with 11-3/4" 42# *11" hole with 8-5/8" 24# casing 7-7/8" hole with 4-1/2" 10.5# | all pertinent details, and give pertinent dates, including estimated date of starical depths for all markers and zones pertinent to this work.)* espectfully requests permission to classing set at 900' with 700 sacks of g set at 1600' with 300 sacks of cem casing set at TD (4400') with 350 s H-40 casing set at 900' with 700 sang set at 1600' with 300 sacks of ce J-55 casing set at TD (4400') with ntered, 8-5/8" intermediate casing was countered, will drill 11" hole to 16 | cement, circulated ent acks of cement cks of cement cks of cement, circulated ment 350 sacks of cement |
| 14. I hereby certify that the foregoing is true and correct | BUREAU GF | /// |
| signed Musty Tella | Tide Operations Results Citations | NAGENEN Pole May 9, 1997 |
| (This space for rederal or State office use) Approved by | Tide | Date |
| Conditions of approval, if any: | | |

10 01 9 ST 11. ...

ROSWELL OFFICE