

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 1300' FWL of Section 10-T6S-R25E (Unit L, NWSW)

5. Lease Designation and Serial No.

10-0304 NM-10263

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Thomas LN Federal #9

9. API Well No.

30-005-63099

10. Field and Pool, or Exploratory Area

Pecos Slope Abo

11. County or Parish, State

Chaves Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Resume drlg, surface casing & cement


- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Resumed drilling a 14-3/4" hole with rotary tools at 9:30 PM 5-23-97.

TD 880'. Reached TD at 2:15 AM 5-25-97. Ran 22 joints of 11-3/4" 42# H-40 (880.83') of casing set at 880'. 1-Texas Pattern notched guide shoe set at 880'. Insert float set at 837'. Cemented with 200 sacks "H", 10#/sack gilsonite, 10% A-10B and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 400 sacks 65-35-6 C, 5#/sack gilsonite, 2% CaCl2 and 1/4#/sack celloflake (yield 1.90, weight 12.6). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.34, weight 14.8). PD 9:30 AM 5-25-97. Bumped plug to 500 psi, OK. Circulated 190 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 11:00 PM 5-25-97. WOC 13 hours and 30 minutes. Reduced hole to 11". Resumed drilling.



RECEIVED
MAY 30 1997
BUREAU OF LAND MGMT
ROSWELL OFFICE

14. I hereby certify that the foregoing is true and correct

Signed

Rusty Allen

Title Operations Technician

Date May 29, 1997

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date