

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division

811 S. 1st Street

Artesia, NM 88210

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-10263

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Thomas LN Federal #9

API Well No.

30-005-63099

10. Field and Pool, or Exploratory Area

Pecos Slope Abo

11. County or Parish, State

Chaves Co., NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 1300' FWL of Section 10-T6S-R25E (Unit 1, NWSW)

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Production casing & cement

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 4220'. Reached TD at 1:15 AM 6-1-97. Ran 94 joints of 4-1/2" 10.5# 8rd J-55 ST&C (4198.51') of casing landed at 4212' with 17.62' landing joint. Regular guide shoe set at 4212'. Float collar set at 4164'. Bottom marker joint set from 3662-3677'. Cemented with 50 sacks "C", 3% SM and 1/4#/sack celloseal (yield 2.87, weight 11.4). Tailed in with 350 sacks Super Modified C, 3/10% FL52, 5#/sack gilsonite and 4#/sack salt (yield 1.71, weight 13.0). PD 7:30 PM 6-1-97. Bumped plug to 1200 psi for 3 minutes, OK. WOC. Released rig at 11:30 PM 6-1-97. NOTE: Sandblasted casing from 3572-4212'. Displaced with 2% KCL.

Waiting on completion unit.

ACCEPTED FOR RECORD
PETER W. CHESTER

JUN 9 1997

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

Date June 4, 1997

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side