

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-63118
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Sacra SA Com
8. Well No. 13
9. Pool name or Wildcat Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	APR 20 1997
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter J : 2310 Feet From The South Line and 1500 Feet From The East Line Section 34 Township 6S Range 25E NMPM Chaves County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3711' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, resume drilling, surface casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 9:00 AM 4-9-97. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of spud. Resumed drilling a 14-3/4" hole with rotary tools at 11:30 PM 4-17-97.

TD 765'. Reached TD at 6:30 PM 4-18-97. Ran 18 joints of 11-3/4" 42# H-40 (748.24') of casing set at 740'. 1-Texas Pattern notched guide shoe set at 740'. Insert float set at 697'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 350 sacks BJ Lite C (65-35-6), 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 250 sacks Class C 2% CaCl2 (yield 1.34, weight 14.8). PD 7:30 AM 4-19-97. Bumped plug to 700 psi, OK. Cement did not circulate. WOC 4 hours. Ran 1". Tagged cement at 245'. Spotted 100 sacks Class C 4% CaCl2. PD 1:30 PM 4-19-97. WOC 1-1/2 hours. Ran 1". Tagged cement at 245'. Spotted 75 sacks Class C 4% CaCl2. PD 3:15 PM 4-19-97. WOC 1 hour. Ran 1". Tagged cement at 215'. Spotted 50 sacks Class C 4% CaCl2. PD

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONTINUED ON NEXT PAGE:

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 24, 1997
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUN
DISTRICT II SUPERVISOR

MAY 5 1997


APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

YATES PETROLEUM CORPORATION
Sacra SA Com #13
Section 34-T6S-R25E
Chaves County, New Mexico

SUNDRY NOTICE CONTINUED:

4:45 PM 4-19-97. WOC 1 hour. Ran 1". Tagged cement at 215'. Spotted 75 sacks Class C 4% CaCl₂. PD 6:15 PM 4-19-97. WOC 1 hour. Ran 1". Tagged cement at 205'. Spotted 75 sacks Class C 4% CaCl₂. PD 7:30 PM 4-19-97. WOC 1 hour. Ran 1". Tagged cement at 200'. Spotted 75 sacks Class C 4% CaCl₂. PD 8:45 PM 4-19-97. WOC 2 hours. Ran 1". Tagged cement at 110'. Spotted 150 sacks Class C 4% CaCl₂. PD 11:30 PM 4-19-97. Circulated 10 sacks to pit. WOC. Cut off and welded on flow nipple. Drilled out at 8:15 AM 4-20-97. WOC 24 hours and 45 minutes. Reduced hole to 11". Resumed drilling.



Rusty Klein
Operations Technician
April 24, 1997