## Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103
Ravised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION P.O. Box 2088

DISTRICT II

Santa Fe, New Mexico 87504-2088

ELL API NO.		V,
30-00	5-63119	
5. Indicate Type of Lo	STATE	FEE X

- DATE -

SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM COI) FOR SUCH PROPOSALS Type of Well:  WILL S ONES  SIDE 1 QZ  RUMB OPPRING WILL S ONES  SIDE 1 QZ  RUMB OPPRING WILL S ONES  SIDE 1 QZ  RUMB OPPRING WILL S ONES  SIDE 1 QZ  Address of Operator 105 SOUTH 4th St., Artesia, NM 88210 APR 0 8 1997  Peos Slope Abo  WILL Leiser F: 2310 Foot From The NOTES SIDE ARM Chaves  WILL Leiser F: 2310 Foot From The NOTES SIDE ARM Chaves  SCIEN 31 TOWNSHIP 6S Rume: 258 NAMTM Chaves  CANCIN SIDE ARM CHAVES  CANCIN SIDE ARM CHAVES  COMMENCE OF INITIATION TO:  SUBSEQUENT REPORT OF:  REFORM REMEDIAL WORK PLUG AND ABANDON SIDE ARM		STATE FEE A
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG MACK 10A (FORM C-101) FOR SUCH PROPOSALS)  Type of Wall:  ONE WALL WALL WALL WALL WALL WALL WALL WAL	ISTRICT III 00 Rio Brazos Rd., Aziec, NM 87410	6. State Oil & Gas Lease No.
Type of Well:  WELL   CANADISC OF WELL   CANADISC O	DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BA	ACK TO A  7. Lease Name or Unit Agreement Name
Name of Operator VATES PETROLEUM CORPORATION  APR 0 8 1997  9. Pool same or Wildcat Pecos Slope Abo  APR 0 8 1997  9. Pool same or Wildcat Pecos Slope Abo  Well Location  F : 2310 Foot From The North Pecos Slope Abo  Well Location  Township 6S Range 75B NMPM Chaves  Section 31 Township 6S Range 75B NMPM Chaves  County  10. Elevation (Show whether DF, RRS, NT, CR, st.)  3908' GR  Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  REFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING  CHANGE PLANS CAMMENCE DPILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB  JUL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB  THER:  OTHER, Resume drilling, surface casing & cmt [X]  TO 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 107 A-11, 10#/ssack gilsonite and 1/4#/sack celloflake (yield 1.50, weight 14.6) and 300 sacks 65-35 Poor, 5#/ssack gilsonite and 1/4#/sack celloflake (yield 1.54, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, OK. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, OK. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  There's ceruly but by following the boom of my incomplete and bold of my incomplete and bold.  THE PREVENTION NO. 505/748-1  THE PREVENTION NO. 505/748-1  THE PREVENTION NO. 505/748-1	Type of Well:	Spell 07
Address of Operator 105 South 4th St., Artesia, NM 88210 APR 0 8 1997 Pecos Slope Abo  Wall Louise  Unit Letter F : 2310 Feet From The No. Pecus Slope Abo  Wall Consider  Unit Letter F : 2310 Feet From The No. Pecus Slope Abo  Wall Consider  On the Section 31 Township 6S Rame 258 NMFM Chaves County  10 Elevation (Show whether DF, RKB, Nf. dR. etc.)  3908' GR  Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  REFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE OF SILLING OPNS. PLUG AND ABANDON CHANGE PLANS  CASING TEST AND CEMENT JOB OTHER: Resume drilling, surface casing 6 cmt [X]  10 Describe Proposed or Completed Operations (Clearly state all periners detail, and give periners datas, including estimated data of starting any proposed word) SER NULE 1103.  Resumed drilling a 14-3/4" hole with rotary tools at 5:45 AM 3-26-97. NOTE: Notified OCD—Artesia answering service.  TD 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 10% sack gilsonite and 1/4 sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1% CaCl2 and 1/4#/sack celloflake (yield 1.90, weight 12.66). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 10:15 PM 3-27-97. Burdled up and tested to 1000 psi for 30 minutes, 0K. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  NOTICE OF INTENTIONAL PROPERTY AND ABANDON TRESHIP AND ABANDON TRES		
Notice of Notice   Ped From The   Notice   Subsequent   Notice   Ped From The   Notice   Section   Show whether DF, REA, RT. CR. etc.	VATES PETROLEUM CORPORATION	
Well Lesses F: 2310 Feet From The North 1.1 Depart 1.2	Address of Operator	<b>1</b>
Unit Letter   F : 2310   Feet From The   North   Nor		1997 recos stope and
Section 31 Township 6S Range 758 NMPM Chaves County   10 Elevalion (Now whether Dr. RRE MT. CR. etc.)   3908' GR   3908' GR   3908' GR   Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data   NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:   REMEDIAL WORK		rest From The West Line
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  RFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB  HER:  DITHER:	Tourntin 6S Range 25	E NMPM Chaves County
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  REFORM REMEDIAL WORK  PLUG AND ABANDON  CHANGE PLANS  COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT  CASING TEST AND CEMENT JOB  OTHER: Resume drilling, surface casing & cmt [X]  CDENTED Proposed or Completed Operations (Clearly state all perinens datails, and give perinens datas, including estimated data of starting any proposed worth) SEE RULE 1103.  RESUMED drilling a 14-3/4" hole with rotary tools at 5:45 AM 3-26-97. NOTE: Notified OCD-Artesia answering service.  TD 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1/4#/sack cacl2 and 1/4#/sack celloflake (yield 1.34, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, oK. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, OK. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  RESUMENT AND THE PRINT NAME  Rusty Klein  TITLE  Operations Technician  DATE April 3, 1997  THE PRINT NAME  Rusty Klein  TITLE OPERATITALE  TITLE OPERATITALE  REMEDIAL WORK  ALTERING CASING	10. Elevation (Show whether DF, RKB, RI,	GR, etc.)
NOTICE OF INTENTION TO:  RFORM REMEDIAL WORK  PLUG AND ABANDON  REMEDIAL WORK  ALTERING CASING  COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT  CASING TEST AND CEMENT JOB  OTHER: Resumed drilling, surface casing & cmt  Tother work) SEE RULE 1103.  Resumed drilling a 14-3/4" hole with rotary tools at 5:45 AM 3-26-97. NOTE: Notified OCD-Artesia answering service.  TD 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1% CaCl2 and 1/4#/sack celloflake (yield 1.90, weight 12.66). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, 0K. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, 0K. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  Resumed drilling.  THE OPERATOR NAME RUSTY Klein		Notice Report or Other Data
REFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: Resume drilling, surface casing & cmt X Commence Drilling of Starting any proposed work) SEE RULE 1103.  Resumed drilling a 14-3/4" hole with rotary tools at 5:45 AM 3-26-97. NOTE: Notified OCD-Artesia answering service.  TD 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1% CaC12 and 1/4#/sack celloflake (yield 1.94, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, OK. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, OK. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  **THEORYRITH NAME** Rusty Klein**  **THEORYRITH NAME***  **THEORYRITH NAME***  **THEORYRITH NAME***  **ALTERING CASING		SUBSECUENT REPORT OF:
MPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: Resume drilling, surface casing & cmt X CASING TEST AND CEMENT JOB OTHER: Resume drilling, surface casing & cmt X work) SER RULE 1103.  Resumed drilling a 14-3/4" hole with rotary tools at 5:45 AM 3-26-97. NOTE: Notified OCD-Artesia answering service.  TD 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1% cacl2 and 1/4#/sack celloflake (yield 1.90, weight 12.66). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, 0K. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, 0K. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  New York Market Mark		
CASING TEST AND CEMENT JOB    CASING TEST AND CEMENT JOB	RFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL	
Describe Proposed or Completed Operations (Clearly state all perinens details, and give perinens dates, including estimated date of starting any proposed work) SEE RULE 1103.  Resumed drilling a 14-3/4" hole with rotary tools at 5:45 AM 3-26-97. NOTE: Notified OCD-Artesia answering service.  TD 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1% CaC12 and 1/4#/sack celloflake (yield 1.90, weight 12.66). Tailed in with 250 sacks "C" and 2% CaC12 (yield 1.34, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, OK. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, OK. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  Resumed drilling.  THE OPERATIONAL RUSTY Klein  THE PRINT NAME  Rusty Klein  TELEPHONE NO. 505/748-1	MI OF WILL FACTOR	
2. Describe Proposed or Completed Operations (Clearly state all pertinent data), and give pertinent datas, including estimated data of starting any proposed work) SEE RULE 1103.  Resumed drilling a 14-3/4" hole with rotary tools at 5:45 AM 3-26-97. NOTE: Notified OCD-Artesia answering service.  TD 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1% CaCl2 and 1/4#/sack celloflake (yield 1.90, weight 12.66). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, 0K. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, 0K. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  Resumed drilling.  The Operations Technician  PATE April 3, 1997  THEORTHINAME  Rusty Klein  THE PHANE NO. 505/748-1	ALL OTTALIET GROWTH	<del></del>
Resumed drilling a 14-3/4" hole with rotary tools at 5:45 AM 3-26-97. NOTE: Notified OCD-Artesia answering service.  TD 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1% CaCl2 and 1/4#/sack celloflake (yield 1.90, weight 12.66). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, OK. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, OK. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  Resumed drilling.  **THE OFFENTINAME** Rusty Klein**  THE OPERATIONAME**  Rusty Klein**  **THE OFFENTINAME**  **	THER: OTHER:	Resume drilling, surface casing & cmt X
Resumed drilling a 14-3/4" hole with rotary tools at 5:45 AM 3-26-97. NOTE: Notified OCD-Artesia answering service.  TD 910'. Reached TD at 5:00 PM 3-27-97. Ran 21 joints of 11-3/4" 40.6# H40 (909.07') of casing set at 902'. 1-Texas Pattern notched guide shoe set at 901'. Insert float set at 857'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1% CaC12 and 1/4#/sack celloflake (yield 1.90, weight 12.66). Tailed in with 250 sacks "C" and 2% CaC12 (yield 1.34, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, OK. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, OK. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  Resumed drilling.  **THE OF FENT NAME**  Rusty Klein**  THE OPERATURAME**  Operations Technician  DATE April 3, 1997  THE OR FENT NAME**  THE OPERATURAME**  THE OP	u arr bir E 1103	
of casing set at 902'. 1-Texas Pattern noticined guide site at 301'. Set at 857'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 300 sacks 65-35 Poz, 5#/sack gilsonite and 1% CaCl2 and 1/4#/sack celloflake (yield 1.90, weight 12.66). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 10:15 PM 3-27-97. Bumped plug to 800 psi, OK. Circulated 220 sacks. WOC. Nippled up and tested to 1000 psi for 30 minutes, OK. Drilled out at 11:00 AM 3-28-97. WOC 12 hours and 45 minutes. Reduced hole to 11".  Resumed drilling.  **Prince Front Name**  Rusty Klein  THE OPERATIONS NO. 505/748-1	Resumed drilling a 14-3/4" hole with rotary tools a	at 5:45 AM 3-26-97. NOTE: Notified
SIONATURE Wisty Klein  THE OPERATIONS Technician  DATE April 3, 1997  THE OFFICIAL THE PHONE NO. 505/748-1	of casing set at 902'. 1-Texas Pattern notched guset at 857'. Cemented with 200 sacks "H", 10% A-1 celloflake (yield 1.51, weight 14.6) and 300 sacks CaCl2 and 1/4#/sack celloflake (yield 1.90, weight and 2% CaCl2 (yield 1.34, weight 14.8). PD 10:15 OK. Circulated 220 sacks. WOC. Nippled up and t Drilled out at 11:00 AM 3-28-97. WOC 12 hours and Resumed drilling.	1, 10#/sack gilsonite and 1/4#/sack 65-35 Poz, 5#/sack gilsonite and 1% 12.66). Tailed in with 250 sacks "C" PM 3-27-97. Bumped plug to 800 psi, ested to 1000 psi for 30 minutes, OK. 45 minutes. Reduced hole to 11".
SIGNATURE Wisty Klein  THE OPERATIONS Technician  DATE April 3, 1997  THE OFFINT NAME  RUSTY Klein  THE OPERATIONS NO. 505/748-1	I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
TYPE OR FRINT NAME Rusty Klein TELEPHONE NO. 505/748-1	Oper	ations Technician April 3, 1997
TYPE OR FRINT NAME.		TREE REPLICATE NO. 505/748-1
(This man for State Use) American at RECAST BY TIM W. GUM	TYPEOR FRINT NAME RUSTY KIEIN	1200-01-10-10-10-10-10-10-10-10-10-10-10-1
	(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM	APR 9 1997

TITLE

CONDITIONS OF AFFROVAL, IF ANY:

APPROVED BY-