

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-005-63119
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter F : 2310 Feet From The North Line and 2310 Feet From The West Line

Section 31 Township 6S Range 25E NMPM Chaves County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3908' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Production casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4100'. Reached TD at 12:30 PM 4-3-97. Ran 93 joints of 4-1/2" 10.5# casing as follows: 16 joints of 4-1/2" 10.5# J-55 sandblasted (694.48') and 77 joints of 4-1/2" 10.5# J-55 varnished (3407.32') (Total 4101.80') of casing set at 4100'. Regular guide shoe set at 4100'. Float collar set at 4054'. Bottom marker set at 3406'. Cemented with 50 sacks C, 3% SM, 1/4#/sack celloflake (yield 2.87, weight 11.4) and 350 sacks Super C (61-15-11), .31#/sack FL52, 8#/sack gilsonite, 3.28#/sack salt, .31#/sack FL25 and 1/4#/sack celloflake (yield 1.69, weight 13.0). PD 4:45 AM 4-4-97. Bumped plug to 1200 psi for 5 minutes, OK. Cement did not circulate. WOC. Released rig at 8:45 AM 4-4-97. NOTE: Displaced with 2% KCL.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 4, 1997  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

APR 9 1997