

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-005-63123
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Davis
8. Well No.	5
9. Pool name or Wildcat	Pecos Slope Abo
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3689' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter N : 990 Feet From The South Line and 1980 Feet From The West Line

Section 12

Township 7S

Range 25E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3689' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Production casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4115'. Reached TD at 4:45 PM 8-5-97. Ran 100 joints of 5-1/2" 15.5# J-55 (4116.97') of casing set at 4108'. Float shoe set at 4108'. Float collar set at 4066'. Bottom marker set at 3483'. Top marker set at 2699'. Cemented with 50 sacks Class C, 3% SM and 1/4#/sack celloflake (yield 2.87, weight 11.4). Tailed in with 500 sacks Super C Modified, 3/10% FL52, 8#/sack gilsonite and 4#/sack salt (yield 1.71, weight 13.0). PD 2:15 AM 8-7-97. Bumped plug to 1250 psi, OK. WOC. Released rig at 5:00 AM 8-7-97. NOTE: Displaced casing with liquid KCL.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Rusty Klein*

TITLE

Operations Technician

DATE Aug. 7, 1997

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

APPROVED BY

TITLE

DATE

AUG 12 1997

CONDITIONS OF APPROVAL, IF ANY: