

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-005-63124

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter E : 1980 Feet From The North Line and 1300 Feet From The West Line

Section 23

Township 7S

Range 25E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3670' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Resume drilling, surface casing & cmt ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 14-3/4" hole with rotary tools at 12:00 midnight 8-9-97.

TD 900'. Reached TD at 8:15 PM 8-10-97. Ran 21 joints of 11-3/4" 42# H-40 8rd ST&C (901.46') of casing set at 900'. 1-Texas Pattern notched guide shoe set at 900'. Insert float set at 859'. Cemented with 200 sacks "H", 10% A-11, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6).and 500 sacks "C" (65-35-6), 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.7). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 3:30 AM 8-11-97. Bumped plug to 700 psi, OK. Circulated 10 sacks. WOC. Cut off and welded on flow nipple. Drilled out at 5:00 PM 8-11-97. WOC.13 hours and 30 minutes. Reduced hole to 11". Resumed drilling.

WOC 13 hrs

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Operations Technician

DATE

Aug. 18, 1997

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

SEP 9 1997

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: