				CISK	<b>^</b> ,
Submit 3 Copies To Appropriate District	State of New Mexico			T	Form C-103
Office <u>District I</u>	Energy, Minerals and Natural Resources			WELLADING	Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 88240 District II				WELL API NO. 30-005-63125	1
811 South First, Artesia, NM 88210 District III	OIL CONSERVATION DIVISION 1220 South St. Francis Dr.			5. Indicate Type of	of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505			STATE [	X FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM				6. State Oil & G	as Lease No.
87505 SUNDRY NOTICES AND REPORTS ON WELLS					Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)  1. Type of Well:				Ziggy ARC State	
Oil Well Gas Well X Other  2. Name of Operator				7. Well No.	
Yates Petroleum Corporation				#1	
3. Address of Operator				8. Pool name or Wildcat	
105 S. 4 <sup>th</sup> Street Artesia, NM 88210				Coyote Queen	
4. Well Location					
Unit Letter B: 990 feet from the North line and 2310 feet from the East line					
Section 12	Γownship <b>11N</b> R	Range	<b>27E</b> N	MPM <b>Chav</b> e	es County
10. Elevation (Show whether DR, RKB, RT, GR, etc.)					
3744' GR  11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
				SSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	X	REMEDIAL WOR		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS		COMMENCE DR	RILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION		CASING TEST A CEMENT JOB	ND	
OTHER:			OTHER:		
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.					
Propose to plug and abandon well as follows:  Notify OCD 24 hrs. prior to any work done  Notify OCD 24 hrs. prior to any work done					
Catalities and a second reliable at 0.005 17501 to prevent the Clarifold report Core Amelican month 1912 07101					
Set a 25 sack plug at 1025-925' to cover the Queen perfs 1034-1139'.  Set a 25 sack plug at 430-330' across the base of the 8-5/8" casing at 380'.  Set a 25 sack plug at 430-330' across the base of the 8-5/8" casing at 380'.					
301 0 23 Sack Surface plug.					
Remove the wellhead and in		er.	outside	Csq. 188-288	
Salt gel mud consisting of 10#  Brine W/25# of gel per bbl  ### ### ##########################					
must be placed between each plug					
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE And the TITLE Engineering Technician DATE January 11, 2002					
Type or print name Susan Herpin Telephone No. 505-748-1471					
(This space for State use)	~00		A -/1/1	1 70	JAN 25 2002
APPPROVED BYConditions of approval, if any.	**	TITL	Leel &	40 e	DATE