

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
811 S. 1st Street
Artesia, NM 88210

45P

RECEIVED

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
Please Designation and Serial No.

NM-2357

6. Indian, Allottee or Tribe Name

1997 JUL -8 A 4 04

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

BUREAU OF LAND MANAGEMENT
ROSWELL OFFICE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FWL of Section 31-T6S-R26E (Unit L, NSW)

8. Well Name and No.

Federal HJ #12

9. API Well No.

30-005-63127

10. Field and Pool, or Exploratory Area

Pecos Slope Abo

11. County or Parish, State

Chaves Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Resume drilling,
surface casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Resumed drilling a 14-3/4" hole with rotary tools at 12:45 PM 6-24-97.

TD 902'. Reached TD at 6:00 PM 6-25-97. Ran 21 joints of 9-5/8" 36# J-55 (901.65') of casing set at 900'. 1-Texas Pattern notched guide shoe set at 900'. Insert float set at 856'. Cemented with 200 sacks Class H, 10% A-10B, 10#/sack gilsonite and 1/4#/sack celloflake (yield 1.51, weight 14.6) and 600 sacks BJ Lite C (65-35-6), 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.66). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.34, weight 14.8). PD 12:00 AM 6-26-97. Bumped plug to 900 psi. Cement did not circulate. WOC. 4-1/4 hours. Ran 1". Tagged cement at 290'. Spotted 100 sacks Class C 4% CaCl2. PD 5:00 AM 6-26-97. WOC 1 hour. Ran 1". Tagged cement at 165'. Spotted 100 sacks Class C 4% CaCl2. PD 6:45 AM 6-26-97. WOC 1-1/4 hours. Ran 1. Tagged cement at 70'. Spotted 100 sacks Class C 4% CaCl2. PD 8:30 AM 6-26-97. Circulated 20 sacks to pit. WOC. Nipped up and tested to 1000 psi for 30 minutes, OK. Drilled out at 10:00 PM 6-26-97. WOC 22 hours. Reduced hole to 7-7/8". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed Rusty Allen

Title Operations Technician


Date July 7, 1997

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____



Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side