

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 E. Elmer Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-006-63132
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-2982

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	7. Lease Name or Unit Agreement Name Angel "AMQ" State
2. Name of Operator United Drilling, Inc.	8. Well No. 1
3. Address of Operator P.O. Box 2488, Roswell NM 88202	9. Pool name or Wildcat Acme-San Andres Southeast
4. Well Location Unit Letter B : 1750 Feet From The South Line and 2310 Feet From The East Section 12 Township 8S Range 27E NMPM Chaves County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) Ground Level 3942	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-8-97 Rig up and start drilling 12-1/4" hole.

5-9-97 Drill to 465'. Run 11 joints of 8-5/8" 24# casing. Cement with 275 sacks, circulate 40 sacks to pit. WOC ? hrs

5-12-97 Drill insert float and continue drilling 7-7/8" hole.

5-16-97 Continue drilling 7-7/8" hole and TD at 2290'.

Run compensated densilog and compensated neutron log and gamma ray logs.
Run 4-1/2" 9.5# casing to TD and cement with 150 sacks of cement. Calculated cement top to be at 1600'.

360 SRS/APD

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Angel Salazar TITLE Vice President DATE 5-19-97
TYPE OR PRINT NAME Angel Salazar TELEPHONE NO. 623-7730

(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

JUN 18 1997

APPROVED BY _____ TITLE _____ DATE _____