DIDIE OF LIEM INTERTED gy, Minerals and Natural Resources Departr

OIL CONSERVATION DIVISION P.O. Box 2088

WELL API NO. 30-005-63133

Form C-103 Revised 1-1-89

DISTRICT II P.O. Drawer DD, Anseia, NM 18210

DISTRICTI P.O. Box 1980, Hobbs, NM 88240

Santa Fe, New Mexico 87504-2088

5. Indicate Type of Lease

DISTRICT III	RECEIVED	STATE X FEE
1000 Rio Brazos Rd., Aziec, NM 87410	KEREMED	6. State Oil & Gas Lesse No. V-2982
SUNDRY NOTICES AND REPORTS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DIFFERENT RESERVOIR. USE "APPLICATION (FORM C-101) FOR SUCH PROPOS	Y FOR PERMIT	7. Lease Name or Unit Agreement Name Angel "AMQ" State
1. Type of Well:	WILL CONTRACTOR VA	
2. Name of Operator	oist. 2	
United Drilling, Inc.		8. Well No.
1. Address of Operator P.O. Box 2488, Roswell NM 88202		9. Pool name or Wildon Acme Southeast San Andres
4. Well Losation		Acine Bodeneast San Andres
Unit Letter B 990 Feet From The No.	rth Line and 23	Peet From The East
Section 12 Township 8S	Range 27E	MPM Chaves Comm
10. Elevation (SAc	w whether DF, RXB, RT, GR, etc.)	
11. Check Appropriate Box to In NOTICE OF INTENTION TO:		port, or Other Data SEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDO		ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING	
PULL OR ALTER CASING CASING TEST AND CEMENT JOB POST FOR 2		
OTHER:	OTHER:	P+H
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including entimated date of starting any proposed work) SEE RULE 1103.		
5-16-97 Rig up and set 10' on conductor pipe. Circulate cement. 5-17-97 Drilling 12¼" hole to 465'. Run 8-5/8" 24# casing to TD. Circulate cement to surface using 275 sacks. Pumped 25 sacks cement to pit. 8-5/8" cemented at 2:15 p.m		
5-20-97 Continued drilling 7-7/8' hole and TD at 2330. Pumped 60 barrels water in well		
Logged well. Well shut in and awaiting orders. 5-21-97 Moved rotary off hole. Well shut in for fluid build up test.		
7-14-97 BJ pumped 25 sacks cement at 2225.8'. 7-14-97 Pumped 25 sacks at 1652.28'. Pumped 25 sacks cement at 1017.34. Pumped 80 sacks cement at 514.20'. Tagged cement at 320'. Pumped 30 sacks cement from 320!		
circulating cement to surface and excess cement to pit.		
Cement job was cemented with Class "C" neat cement with 3% calcium chloride.		
I hereby corally that the information above is true and complete to the best of my kin	owiedge and bailef.	
SIGNATURE Grupel Alan	Wice Presi	dent 7-31-97
TYPE OR PRINT NAME Angel Salazar		TZLEPHONE NO.623-7730
(True space for State Use)	~d^ 4	