

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

L CONSERVATION DIVISIO

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-005-63146
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name Hartlad B
2. Name of Operator Hanson Operating Company, Inc.	8. Well No. #7
3. Address of Operator P.O. Box 1515, Roswell, NM 88202-1515	9. Pool Name or Wildcat Diablo San Andres
4. Well Location Unit Letter <u>L</u> : <u>1650</u> Feet From The <u>South</u> Line and <u>330</u> Feet From The <u>West</u> Line Section <u>22</u> Township <u>10S</u> Range <u>27E</u> NMPM Chaves County	10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-20-97 Ran 516' of 8 5/8" casing, 1 guide shoe, 1 shoe jnt., 1 insert float. Cement as follows: Pumped 75 bbls. water to clean pipe and hole. Pumped 10 sxs of Gel water, 12 sxs Gel spacer, 320 sxs of Class C 2% CCL. Plugged down at 12 am, circulated 60 sxs to pit. Tested casing at 500 psi for 15 min., held ok. *WOC? h*

9-26-97 Ran 5 1/2" casing, 1 guide shoe, 1 shoe joint 30.4', 1 float collar 1.1', 77 jnts. totaling 2765'. Top of float collars 2765'. Cement as follows: Cir. hole pumped 25 sxs fresh water gel. Cemented with 280 sxs of Class C tailend, cemented 200 sxs supper C. Plugged down at 6:30 pm. Circulated 30 sxs to pit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Betsy Speer TITLE Production Analyst DATE 10-03-97

TYPE OR PRINT NAME Betsy Speer TELEPHONE NO. 622-7330

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE OCT 20 1997

CONDITIONS OF APPROVAL, IF ANY: