

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-005-63150
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Jamie Com
8. Well No.	2
9. Pool name or Wildcat	Pecos Slope Abo

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter I : 1980 Feet From The South Line and 330 Feet From The East Line Section 33 Township 5S Range 25E NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3699' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4120'. Reached TD at 2:45 AM 12-18-99. Ran 97 joints of 4-1/2" 10.5# J-55 (4126.78') of casing set at 4120'. Regular guide shoe set at 4120'. Float collar set at 4077'. Cemented with 1200 sacks Premium Plus, 1% CaCl2 and 1% zone seal 2000 with N2 (yield 1.32, weight 14.8). Tailed in with 500 sacks Premium Plus, 1% CaCl2 and 1% zone seal with N2 (yield 1.32, weight 14.8) and 75 sacks Premium Plus with 2% CaCl2. PD 11:34 AM 12-19-99. Bumped plug to 1500 psi for 2 minutes. Circulated 240 sacks. WOC. Released rig at 2:00 PM 12-19-99.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Dec. 23, 1999
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Jim W. Ginn DISTRICT SUPERVISOR District Supervisor DATE 1-4-00
CONDITIONS OF APPROVAL, IF ANY: