

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

NEW MEXICO CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-005-63166

5. Indicate Type of Lease

STATE ☐FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒GAS
WELL ☐

OTHER

2. Name of Operator

Hanson Operating Company, Inc.

3. Address of Operator

P.O. Box 1515, Roswell, NM 88202-1515

4. Well Location

Unit Letter D : 990 Feet From The North Line and 990 Feet From The West LineSection 1Township 9SRange 29E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3999

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐COMMENCE DRILLING OPNS. ☐PLUG AND ABANDONMENT ☒PULL OR ALTER CASING ☐CASING TEST AND CEMENT JOB ☐OTHER: ☐OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 2-19-98 Ran 24 jts. of 8 5/8 24# casing. Ran as follows: 1 guide shoe, 1 shoe jnt. 42.5', 1 insert float, then 23 jnts. of casing. Landed and cemented at 978', cement as follows: lead cement 250 sxs 35-65 6+1/4#/GF and 2% CACL2, tail cement 225 sxs Class C + 2% CACL2. Circulated 34 sxs to pit.
- 2-28-98 TD 3680', set 100' plug, 39 sxs at 3680'. Pulled up to 2300', set 100' plug with 40 sxs, pulled 40 jts of pipe. Waited 2 hrs., ran back in hole and tagged top of plug at 2240'. Pulled up to 1028'. Pumped 100' plug with 50 sxs. Pulled 20 jts of pipe. Waited 2 hrs. ran back in hole and tagged plug at 905'. Pulled up to surface and set 15 sxs plug in top 30' of 8 5/8" casing. Circulated 4 sxs of cement to pit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Betsy Speer

TITLE Production Analyst

DATE 3-3-98

TYPE OR PRINT NAME

Betsy Speer

505-622-7330
TELEPHONE NO.

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 21 2002