

455
G

DISTRICT I

P.O. Box 1980, Hobbs, NM 88241-1980

DISTRICT II

811 S. First Street, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, New Mexico 87505

WELL API NO.

30-005-63178

5. Indicate Type of Lease

STATE

☒

FEE

☐

6. State Oil & Gas Lease No.

LG-7983

7. Lease Name or Unit Agreement Name

JAN STATE

8. Well No.

3

9. Pool Name or Wildcat

FOOR RANCH; PRE PERMIAN GAS

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
OIL ☐ GAS ☐
WELL ☐ WELL ☒ OTHER ☐

2. Name of Operator
ELK OIL COMPANY

3. Address of Operator
POST OFFICE BOX 310, ROSWELL, NEW MEXICO 88202-0310

4. Well Location
Unit Letter B : 660 Feet From The NORTH Line and 1650 Feet From The EAST Line
Section 36 Township 8 SOUTH Range 26 EAST NMPM CHAVES County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3946' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)
SEE RULE 1103

Spud well at 5:00 P.M. on 10/11/98. Drill a 12 1/4" hole to 1035'. Ran (27 joints) of 8 5/8", 24# casing. Cemented with 450 sxs Halliburton Lite Premium Plus with 1/4# Flocele and 5# Gilsonite with 2% CaCl2. Tailed by 200 sxs Premium Plus with 2% CaCl2. Plug down at 5:45 A.M. on 10/13/98. Circulated 75 sxs. WOC 18 hours. Tested to 1000# for 30 minutes, test okay. Resume drilling a 7 7/8" hole.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE PRESIDENT DATE 10/20/98
TYPE OR PRINT NAME JOSEPH J. KELLY TELEPHONE NO. 505-623-3190

(This space for State Use)

APPROVED BY SUPERVISOR, DISTRICT II TITLE DATE 10-22-98
CONDITIONS OF APPROVAL, IF ANY: