

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-005-63189
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name Twin Lakes San Andres Unit
Well No. 326
Pool name or Wildcat Twin Lakes San Andres (Associated)

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
Name of Operator HANAGAN PETROLEUM CORPORATION	
Address of Operator P.O. BOX 1737 - ROSWELL, NM - 88202-1737	
Well Location Unit Letter <u>N</u> : <u>110</u> Feet From The <u>SOUTH</u> Line and <u>2410</u> Feet From The <u>WEST</u> Line 31 Section 8s Township 29e Range NMPIW CHAVES County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 4009 KB	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

### SUBSEQUENT REPORT OF:


REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/27/98 - MIRU United Drilling Co. Rig #10 - drill 12.25" hole to 118' w/air - run 3jts 8.625" 24#/ft casing to TD - RU Roswell Ready Mix & cement w/3yds Redi-Mix to surface - RD United Rig #10

12/1/98 - MIRU United Drilling Co. Rig #4 - drill 7.875" hole to 2855'

12/5/98 - TD 7.875" hole @ 2855' - Run 65jts of 5.5", 15.50#/ft J55 casing w/shoe @ 2850' (KB) -RU Halliburton & cement w/600sx Interfill "C" lead cement, tailed in w/300sx 50/50 Premium Plus Poz cement w/5#/sk salt & 0.6% Halad 322, circulate 124sx cement to pits - Release rig



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Michael G. Hanagan TITLE President DATE 12-14-98  
TYPE OR PRINT NAME Michael G. Hanagan

TELEPHONE NO. 623-5053

(This space for State Use)

APPROVED BY SUPERVISOR, DISTRICT II TITLE \_\_\_\_\_ DATE 1-25-99  
CONDITIONS OF APPROVAL, IF ANY: